

66794538

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

- INSTRUCTION BOOK 3518

BM FORM

proof of purchase



owner registration sticker




ORDER NO. **25716**

BARREL LENGTH **24"**

CAPACITY **6**

G6794538

UPC



GUN SERIAL #

G 6794538

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		10-27-08	SP
430	ASSEMBLE TO STOCK		10-27-08	SP
440	PROOF		10-27-08	SP
460	CHECK HEADSPACE		10-27-08	SP
470	DIS-ASSEMBLE ACTION		10-27-08	SP
472	SERIALIZE BOLT HANDLE		10-28-08	RSW
475	DRILL AND TAP SIGHT HOLES		10-28-08	SP
480	MAGNAFLUX BBL ACTION		10-29-08	SP
490	MAGNAFLUX BOLT			
500	ROLLMARK CALIBER		10/29/08	RT
520	GOFF BLAST BBL / REC			
542	APPLY COATINGS (BARREL ACTION)		10-30	SP
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		11-3-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		11-3-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		11-3-08	SP
	D) OIL FIRING PIN ASSEMBLY		11-6-08	RSW
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS		
F004 REV 5/2006				

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>30</u> <u>30</u> <u>25</u>	11-13-08	RN
CONT.	G) SAFETY OFF FORCE 2 LBS MIN	<u>40</u> <u>40</u> <u>40</u>	11-13-08	RN
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.023</u> <u>.023</u> <u>.023</u>	11-13-08	RN
	J) ASSEMBLE STOCK		11-6-08	RN
	K) ASSEMBLE SWIVEL STUDS		11-13-08	RN
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	11-7-08	TC
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		11-7-08	RN
670	FINAL INSPECTION A) HEADSPACE		11-13-08	RN
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.51</u> <u>2.59</u> <u>2.56</u> <u>2.56</u> <u>2.47</u>	11-7-08	TC
	C) FUNCTION		11-13-08	RN
690	PACK		11/17/08	FM

F004 REV 5/2006

BARBER - M24 0072719

 AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)

3.00 LBS (plus or minus 0.75 LBS)

4.00 LBS (plus or minus 1.00 LBS)

 DATE 10-28-08

 TESTER TAE

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	231	248		289	
PULL #2	232	238		288	
PULL #3	228	232		288	
PULL #4	228	228		277	
PULL #5	224	244		275	
TOTAL	1149	1190		1417	
AVERAGE	229.8	238		283	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	306	317		
PULL #2	317	312		
PULL #3	311	309		
PULL #4	308	308		
PULL #5	305	348		
TOTAL	1549	1543 1937		
AVERAGE	309	387		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	343 421	421		425
PULL #2	427	418		420
PULL #3	429	421		426
PULL #4	425	418		426
PULL #5	426	421		425
TOTAL	2141	2135 2099		2128
AVERAGE	428	419		425