

G6794618

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

- INSTRUCTION BOOK 3518

BM FORM

proof of purchase



owner registration sticker




ORDER NO. **25716**

BARREL LENGTH **24"**

CAPACITY **6**

G6794618

UPC



GUN SERIAL #

G6794618

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		10-27-08	SP
430	ASSEMBLE TO STOCK		10-27-08	SP
440	PROOF		10-27-08	SP
460	CHECK HEADSPACE		10-27-08	SP
470	DIS-ASSEMBLE ACTION		10-27-08	SP
472	SERIALIZE BOLT HANDLE		10-28-08	BSN
475	DRILL AND TAP SIGHT HOLES		10-28-08	SP
480	MAGNAFLUX BBL ACTION		10/29/08	SP
490	MAGNAFLUX BOLT		10/27/08	PK
500	ROLLMARK CALIBER		10/29/08	RT
520	GOFF BLAST BBL / REC		10/29/08	DG
542	APPLY COATINGS (BARREL ACTION)		11-3	
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		11-3-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		11-3-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		11-3-08	SP
	D) OIL FIRING PIN ASSEMBLY		11-11-08	BSN
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS		
F004 REV 5/2006				

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>3.5</u> <u>3.5</u> <u>4.0</u>	11-18-08	LD
CONT.				
	G) SAFETY OFF FORCE 2 LBS MIN	<u>5.0</u> <u>5.0</u> <u>5.0</u>	11-18-08	LD
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.034</u> <u>.034</u> <u>.034</u>	11-18-08	LD
	J) ASSEMBLE STOCK		11-11-08	LSN
	K) ASSEMBLE SWIVEL STUDS		11-18-08	LD
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	11-12-08	TC
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		11-12-08	JS
670	FINAL INSPECTION A) HEADSPACE		11-18-08	LD
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.68</u> <u>2.63</u> <u>2.61</u> <u>2.61</u> <u>2.57</u>	11-14-08	TC
	C) FUNCTION		11-18-08	LD
690	PACK		12/11/08	Fm

F004 REV 5/2006

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)

3.00 LBS (plus or minus 0.75 LBS)

4.00 LBS (plus or minus 1.00 LBS)

DATE

11-6-08

TESTER

TAE

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	271	284		225	
PULL #2	274	284		235	
PULL #3	276	266		229	
PULL #4	297	298		232	
PULL #5	295	272		243	
TOTAL	1408	1403		1164	
AVERAGE	282	272		232	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	326	318		
PULL #2	319	317		
PULL #3	332	316		
PULL #4	322	320		
PULL #5	323	320		
TOTAL	1944	1907		
AVERAGE	388	381		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	413	431		403
PULL #2	421	424		408
PULL #3	426	422		404
PULL #4	416	421		407
PULL #5	419	429		404
TOTAL	2095	2127		2029
AVERAGE	419	425		405