

66794629

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase



owner registration sticker




ORDER NO. **86470**

BARREL LENGTH 24"

CAPACITY 6

G6794629

UPC



BM FORM

GUN SERIAL #

G 6794629

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		9-29-08	SP
430	ASSEMBLE TO STOCK		9-29-08	SP
440	PROOF		9-29-08	SP
460	CHECK HEADSPACE		9-29-08	SP
470	DIS-ASSEMBLE ACTION		9-29-08	SP
472	SERIALIZE BOLT HANDLE		9-30-08	SP
475	DRILL AND TAP SIGHT HOLES		10/1/08	FM
480	MAGNAFLUX BBL ACTION		10/2/08	SP
490	MAGNAFLUX BOLT		10/2/08	SP
500	ROLLMARK CALIBER		10/2/08	RT
520	GOFF BLAST BBL / REC		10/2/08	DC
542	APPLY COATINGS (BARREL ACTION)		10-3	
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		10-13-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		10-13-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		10-13-08	SP
	D) OIL FIRING PIN ASSEMBLY		10-13-08	SP
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS		

F004 REV 5/2006

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>4.0</u> <u>4.0</u> <u>4.0</u>	12-11-08	L.N.
CONT.	G) SAFETY OFF FORCE 2 LBS MIN	<u>3.0</u> <u>3.0</u> <u>4.0</u>	12-11-08	L.N.
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.034</u> <u>.034</u> <u>.034</u>	12-11-08	L.N.
	J) ASSEMBLE STOCK		10-13-08	L.P.D.
	K) ASSEMBLE SWIVEL STUDS		12-11-08	L.N.
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	12-10-08	L.P.D.
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION <i>N/A</i>		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		12-10-08	RP
670	FINAL INSPECTION A) HEADSPACE		12-11-08	L.N.
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.74</u> <u>2.77</u> <u>2.63</u> <u>2.78</u> <u>2.68</u>	12-11-08	LSW
	C) FUNCTION		12-11-08	L.N.
690	PACK		12-18-08	LSW

F004 REV 5/2006

BARBER - M24 0073741
**AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS**

2.50 LBS (plus or minus 0.50 LBS)
3.00 LBS (plus or minus 0.75 LBS)
4.00 LBS (plus or minus 1.00 LBS)

 DATE 10-10-08

 TESTER TAE

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	268	288		234	
PULL #2	259	278		222	
PULL #3	273	263		242	
PULL #4	271	271		242	
PULL #5	262	285		229	
TOTAL	1333	1385		3169	
AVERAGE	266	277		233	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	368	355		
PULL #2	389	332		
PULL #3	310	329		
PULL #4	319	329		
PULL #5	350	322		
TOTAL	1716	1667		
AVERAGE	343	333		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	417	442		444
PULL #2	446	427		424
PULL #3	435	421		431
PULL #4	448	428		414
PULL #5	451	426		412
TOTAL	2197	2144		2125
AVERAGE	439	428		425