

0494640

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase



owner registration sticker



BM FORM


ORDER NO. **86470**

BARREL LENGTH 24"

CAPACITY 6

G6794640

UPC



GUN SERIAL #

G 6794640

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		9-29-08	SPD
430	ASSEMBLE TO STOCK		9-29-08	SP
440	PROOF		9-29-08	SPD
460	CHECK HEADSPACE		9-29-08	SPD
470	DIS-ASSEMBLE ACTION		9-29-08	SPD
472	SERIALIZE BOLT HANDLE		9-30-08	FBN
475	DRILL AND TAP SIGHT HOLES		10/1/08	FM
480	MAGNAFLUX BBL ACTION		10/2/08	RB
490	MAGNAFLUX BOLT		10/2/08	MR
500	ROLLMARK CALIBER		10/2/08	RT
520	GOFF BLAST BBL / REC		10/2/08	DG
542	APPLY COATINGS (BARREL ACTION)		10/3	
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		10-3-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		10-3-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		10-3-08	SP
	D) OIL FIRING PIN ASSEMBLY		10-13-08	SPD
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS		

F004 REV 5/2006

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>40</u> <u>40</u> <u>40</u>	12-12-08	L.N.
CONT.				
	G) SAFETY OFF FORCE 2 LBS MIN	<u>50</u> <u>50</u> <u>50</u>	12-12-08	L.N.
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.025</u> <u>.025</u> <u>.025</u>	12-12-08	L.N.
	J) ASSEMBLE STOCK		10-13-08	L.P.D.
	K) ASSEMBLE SWIVEL STUDS		12-12-08	L.N.
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	12-11-08	L.P.D.
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		12-11-08	R.P.
670	FINAL INSPECTION A) HEADSPACE		12-12-08	L.N.
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>237</u> <u>240</u> <u>234</u> <u>240</u> <u>238</u>	12-12-08	L.N.
	C) FUNCTION		12-12-08	L.N.
690	PACK		12/16/08	ESN

F004 REV 5/2006

BARBER - M24 0073845
**AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS**

2.50 LBS (plus or minus 0.50 LBS)
3.00 LBS (plus or minus 0.75 LBS)
4.00 LBS (plus or minus 1.00 LBS)

DATE

10-10-08

TESTER

TAE

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS	COMMENTS
PULL #1	228	260	235	
PULL #2	217	249	251	
PULL #3	204	255	260	
PULL #4	224	262	260	
PULL #5	245	279	230	
TOTAL	1341	1305	1236	
AVERAGE	268	261	247	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES	COMMENTS
PULL #1	335	346	
PULL #2	329	356	
PULL #3	355	331	
PULL #4	329	343	
PULL #5	385	313	
TOTAL	1681	1689	
AVERAGE	336	337	

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	445	463		425
PULL #2	417	417		424
PULL #3	440	425		408
PULL #4	440	409		475
PULL #5	463	450		459
TOTAL	2205	2164		2211
AVERAGE	441	432		442