

G 679 4699

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase



owner registration sticker



BM FORM


ORDER NO. **86470**

BARREL LENGTH 24"

CAPACITY 6

G6794699

UPC



INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL #

G 679 4699

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		11-11-08	SPD
430	ASSEMBLE TO STOCK		11-11-08	SP
440	PROOF		11-11-08	SPD
460	CHECK HEADSPACE		11-11-08	SPD
470	DIS-ASSEMBLE ACTION		11-11-08	SPD
472	SERIALIZE BOLT HANDLE	MAGNA-FLUX	11-12-08	RTZ
475	DRILL AND TAP SIGHT HOLES		11-12-08	SP
480	MAGNAFLUX BBL ACTION	OPERATOR 	11/17/08	
490	MAGNAFLUX BOLT			
500	ROLLMARK CALIBER		11/17/08	RT
520	GOFF BLAST BBL / REC			
542	APPLY COATINGS (BARREL ACTION)		11/21	
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		11-25-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		11-25-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		11-25-08	SP
	D) OIL FIRING PIN ASSEMBLY		12-30-08	RTZ
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS			

F004 REV 5/2006

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>4.0</u> <u>4.0</u> <u>4.0</u>	1-7-09	R.N.
CONT.				
	G) SAFETY OFF FORCE 2 LBS MIN	<u>6.0</u> <u>6.0</u> <u>5.0</u>	1-7-09	R.N.
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.024</u> <u>.024</u> <u>.024</u>	1-7-09	R.N.
	J) ASSEMBLE STOCK		12-30-08	RTZ
	K) ASSEMBLE SWIVEL STUDS		1-7-09	R.N.
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	1-6-09	R.P.D.
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		1-6-09	RP
670	FINAL INSPECTION A) HEADSPACE		1-7-09	R.N.
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.33</u> <u>2.45</u> <u>2.39</u> <u>2.33</u> <u>2.41</u>	1-7-09	TC
	C) FUNCTION		1-7-09	R.N.
690	PACK		1-21-09	R.N.

F004 REV 5/2006

BARBER - M24 0074498

 AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

 2.50 LBS (plus or minus 0.50 LBS)
 3.00 LBS (plus or minus 0.75 LBS)
 4.00 LBS (plus or minus 1.00 LBS)

 DATE 11-19-08

 TESTER FAE

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	258	275		269	
PULL #2	278	252		267	
PULL #3	285	264		274	
PULL #4	287	260		257	
PULL #5	268	262		260	
TOTAL	1376	1313		1327	
AVERAGE	275	262		265	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	322	319		
PULL #2	318	321		
PULL #3	320	334		
PULL #4	324	323		
PULL #5	319	324		
TOTAL	1603	1621		
AVERAGE	320	324		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	431	442		411
PULL #2	440	433		411
PULL #3	438	437		409
PULL #4	433	432		414
PULL #5	442	425		409
TOTAL	2184	2169		2054
AVERAGE	436	433		410