

G636 1004

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

- INSTRUCTION BOOK 3518

DD FORM

proof of purchase



owner registration sticker




ORDER NO. 25716

BARREL LENGTH 24"

CAPACITY 6

G6361004

UPC



BRONZE PLATE
INSTRUCTION - 6636
STAMP - 6636
STAMP - 6636
STAMP - 6636

Remington
M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

SERIAL NO.
66361004
ORDER NO.
25716
DO
11PY

MADE IN ITALY BY: Remington-Union, Inc. - Italy (U.S. Pat. & Reg. Off.) Marca Registrata. No. 66361004


5716 66361004

ORDER 25716
M/24 7.62 NATO S.W.S. (COMPLETE SYSTI
UPC



ORDER 25716
M/24 7.62 NATO S.W.S. (COMPLETE SYSTI
UPC



SERIAL NO.

66361004

INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL # G6361004

OP #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK		4-1-04	RK
600	PROOF		4-1-04	RTL
607	CHECK HEADSPACE	MAGNA-FLUX INSPECTED	4-1-04	RTL
610	DIS-ASSEMBLE GUN	APR 1 2004	4-1-04	RTL
612	MAGNAFLUX BBL ACTION MAGNAFLUX BOLT	OPERATOR <u>RK</u>		
615	ROLLMARK CALIBER		4/5/04	JS
617	DRILL AND TAP SIGHT HOLES		4-2-04	TRL
620	APPLY COATINGS (BARREL ACTION)		4-7	TH
	(BOLT)		4-7	TH
625	FINAL ASSEMBLY			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		4-26-04	RTL
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		4-26-04	RTL
	C) INSPECT EJECTOR HOLE FOR CHAMFER		4-26-04	RTL
	D) OIL FIRING PIN ASSEMBLY		4-26-04	RTL
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS		

OP # OPERATION NAME			READINGS			DATE	INITIAL		
625	F) SAFETY ON FORCE	2 LBS MIN 10 LBS MAX	7 ⁰	7 ⁰	7 ⁰	5-24-04	RTZ		
CONT.									
	G) SAFETY OFF FORCE	2 LBS MIN	2 ⁰	2 ⁰	2 ⁰	5-24-04	RTZ		
	H) TRIGGER PULL TEST AND RETAINABILITY								
	I) FIRING PIN INDENT	.020 MIN	.022	.022	.022	5-24-04	RTZ		
	J) ASSEMBLE STOCK					4-26-04	RTZ		
	K) ASSEMBLE SWIVEL STUDS					6-9-04	RTZ		
	L) ATTACH FRONT AND REAR SIGHT ASSY'S					4-26-04	RTZ		
	M) IRON SIGHT ALIGNMENT					4-26-04	RTZ		
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER					4-26-04	RTZ		
640	GALLERY TEST AND TARGET		PASS		FAIL	4-30-04	TRW		
	MALFUNCTION		CORRECTION			4-30-04	TRW		
	MALFUNCTION		CORRECTION			4-30-04	TRW		
	MALFUNCTION		CORRECTION			4-30-04	TRW		
	MALFUNCTION		CORRECTION			4-30-04	TRW		
645	INSPECT FOR LIVE AMMO					4-30-04	TRW		
655	FINAL INSPECTION A) HEADSPACE					6-9-04	RTZ		
	B) TRIGGER PULL	+/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	2.76	2.78	2.89	2.91	2.83	5/24/04	DA
	C) FUNCTION					6-9-04	RTZ		
660	PACK					6-10-04	DA		

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)
3.00 LBS (plus or minus 0.75 LBS)
4.00 LBS (plus or minus 1.00 LBS)

SERIAL NO. _____

DATE 4-22-04

TESTER Reu

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	2.39	2.30		2.14	
PULL #2	2.24	2.25		2.16	
PULL #3	2.31	2.27		2.17	
PULL #4	2.23	2.24		2.15	
PULL #5	2.24	2.22		2.17	
TOTAL	11.41	11.28		10.79	
AVERAGE	2.28	2.25		2.16	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	3.17	2.99		
PULL #2	3.19	3.24		
PULL #3	3.21	3.25		
PULL #4	3.21	3.23		
PULL #5	3.15	3.22		
TOTAL	15.93	15.93		
AVERAGE	3.18	3.18		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	4.40	4.10		4.07
PULL #2	4.15	4.12		4.19
PULL #3	4.10	4.13		4.22
PULL #4	4.09	4.12		4.14
PULL #5	4.12	4.07		4.11
TOTAL	20.86	20.54		20.73
AVERAGE	4.17	4.11		4.15

SNIPER WEAPON SYSTEM - UNIQUE STATISTICAL INFORMATION

FIREARM SERIAL NUMBER / DATASET NAME: G6361004.___0
FILE DATE AND TIME: 04/30/2004 05:58

THE FOLLOWING DATA IS ALL REPORTED IN UNITS OF INCHES

The Average X Centroid of the Five Target Set:	0.013
The Average Y Centroid of the Five Target Set:	-0.176
The Average Point of Impact of the Five Target Set:	0.176
The Average Mean Radius of the Five Target Set:	0.833
The Distance from POA to Centroid Target #1:	0.329
The Distance from Centroid Target #2 to Centroid Target #1:	0.267
The Distance from Centroid Target #3 to Centroid Target #1:	0.175
The Distance from Centroid Target #4 to Centroid Target #1:	0.447
The Distance from Centroid Target #5 to Centroid Target #1:	0.117


BARBER - M24 0081978

SERIAL NUMBER: G6361004. __ 0
 TARGET NUMBER: 1
 FILE DATE: 04/30/2004
 FILE TIME: 05:58

X CENTROID: 0.001
 Y CENTROID: -0.328
 POA TO CENTROID: 0.329
 HORZ SPREAD: 1.693
 VERT SPREAD: 3.259
 GROUP SPREAD: 3.264
 MIN RADIUS: 0.308
 MAX RADIUS: 2.117
 MEAN RADIUS: 0.962
 # IN 1 IN DIAMETER: 2
 # IN 2 IN DIAMETER: 14
 # in 3 IN DIAMETER: 18

POINT#	X	Y
1:	0.046	-2.445
2:	0.704	-1.297
3:	0.917	-0.699
4:	-0.739	-0.725
5:	0.166	-0.068
6:	-0.614	-0.173
7:	-0.330	0.222
8:	-0.353	0.447
9:	-0.125	0.586
10:	0.181	0.652
11:	-0.134	0.814
12:	0.229	0.644
13:	-0.281	0.438
14:	-0.388	0.249

POINT#	X	Y
15:	-0.507	-0.093
16:	0.212	-0.010
17:	-0.776	-0.724
18:	0.798	-1.358
19:	0.916	-0.736
20:	0.098	-2.294



TARGET APPROX 1/2 SCALE

SERIAL NUMBER: G6361004. __0

TARGET NUMBER: 2

FILE DATE: 04/30/2004

FILE TIME: 05:58

POINT#	X	Y
1:	0.950	-0.648
2:	0.604	-0.458
3:	0.318	-0.040
4:	0.503	0.741
5:	-0.464	-1.311
6:	-0.330	-0.371
7:	0.036	0.295
8:	-0.303	0.350
9:	-0.571	0.159
10:	-0.735	0.668

X CENTROID: 0.001

Y CENTROID: -0.062

POA TO CENTROID: 0.062

HORZ SPREAD: 1.685

VERT SPREAD: 2.052

GROUP SPREAD: 2.268

MIN RADIUS: 0.318


MAX RADIUS: 1.333

MEAN RADIUS: 0.741

IN 1 IN DIAMETER: 3

IN 2 IN DIAMETER: 7

in 3 IN DIAMETER: 10



TARGET APPROX 1/2 SCALE

SERIAL NUMBER: G6361004. __0

TARGET NUMBER: 3

FILE DATE: 04/30/2004

FILE TIME: 05:58

X CENTROID: 0.053

Y CENTROID: -0.162

POA TO CENTROID: 0.170

HORZ SPREAD: 1.789

VERT SPREAD: 2.520

GROUP SPREAD: 2.664

MIN RADIUS: 0.174

MAX RADIUS: 1.704


MEAN RADIUS: 0.843

IN 1 IN DIAMETER: 3

IN 2 IN DIAMETER: 6

in 3 IN DIAMETER: 9

POINT#	X	Y
1:	0.877	-1.653
2:	-0.373	-1.110
3:	0.715	-0.519
4:	0.336	-0.511
5:	0.156	-0.302
6:	0.063	0.289
7:	0.248	0.867
8:	0.024	0.830
9:	-0.606	0.173
10:	-0.912	0.321



TARGET APPROX 1/2 SCALE

SERIAL NUMBER: G6361004. __0

TARGET NUMBER: 4

FILE DATE: 04/30/2004

FILE TIME: 05:58

POINT#	X	Y
1:	0.215	-0.709
2:	0.902	-0.237
3:	0.455	-0.094
4:	0.208	-0.272
5:	0.491	0.394
6:	0.532	0.496
7:	-0.389	0.658
8:	-0.532	-0.074
9:	-1.100	-0.121
10:	-0.734	1.144

X CENTROID: 0.005

Y CENTROID: 0.118

POA TO CENTROID: 0.119

HORZ SPREAD: 2.002

VERT SPREAD: 1.853

GROUP SPREAD: 2.141

MIN RADIUS: 0.440


MAX RADIUS: 1.264

MEAN RADIUS: 0.760

IN 1 IN DIAMETER: 2

IN 2 IN DIAMETER: 8

in 3 IN DIAMETER: 10



TARGET APPROX 1/2 SCALE

SERIAL NUMBER: G6361004. __0

TARGET NUMBER: 5

FILE DATE: 04/30/2004

FILE TIME: 05:58

X CENTROID: 0.006

Y CENTROID: -0.446

POA TO CENTROID: 0.446

HORZ SPREAD: 1.937

VERT SPREAD: 2.071

GROUP SPREAD: 2.360

MIN RADIUS: 0.471

MAX RADIUS: 1.619


MEAN RADIUS: 0.861

IN 1 IN DIAMETER: 1

IN 2 IN DIAMETER: 7

in 3 IN DIAMETER: 9

POINT#	X	Y
1:	0.239	-2.048
2:	0.719	-1.473
3:	0.811	-0.122
4:	0.620	-0.139
5:	0.338	-0.001
6:	0.051	0.023
7:	-0.232	0.015
8:	-0.435	-0.152
9:	-0.928	-0.438
10:	-1.126	-0.123



TARGET APPROX 1/2 SCALE