

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum 7mm RM

Project: 241314

Rifle: A-12

TLW #: TLW1447

Date: 5 / 25 / 04Inspector: SWRound Level: 70.1

- ☒ Measure Headspace Min +.003
- ☒ Inspect Take Down Screws for loosening. Front Screw 0 Turn
- ☒ Sear Engagement: 1st. .0342 2nd. .0345 3rd. .0343 Ave. .0343 spec. .025" to .030"
- ☐ Reset Sear Engagement if Required: 1st. 2nd. 3rd. Ave.
- ☒ Trigger Pull: 1st. 3.823 2nd. 3.879 3rd. 3.881 Ave. 3.861 spec- 4.5 lb. to 5.5 lb.
- ☒ Reset Trigger Pull if Required: 1st. 5.481 2nd. 5.234 3rd. 5.369 Ave. 5.361
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: Locking lugs normal wear. OK
- ☒ Inspect stock for any signs of cracking or other failure: OK
- ☐ Other items of note:

TLW1216

Remington Confidential

ET21600