

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum 7mm RM

Project: 241314

Rifle: A-13

TLW #: TLW1447

Date: 5 / 24 / 04Inspector: SWRound Level: 1201

- ☒ Measure Headspace Min 4.003
- ☒ Inspect Take Down Screws for loosening. Front screw 1/4 Turn 83
- ☐ Sear Engagement: 1st. .0364 2nd. .0362 3rd. .0362 Ave. .03626 spec- .025" to .030"
- ☐ Reset Sear Engagement if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____
- ☒ Trigger Pull: 1st. 4.990 2nd. 4.960 3rd. 5.013 Ave. 4.987 spec- 4.5 lb. to 5.5 lb.
- ☐ Reset Trigger Pull if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: Locking lugs normal wear OK
- ☐ Inspect stock for any signs of cracking or other failure: OK
- ☐ Other items of note: _____

TLW1216

Remington Confidential

ET21616