

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum 7mm RM

Project: 241314

Rifle: A-14

TLW #: TLW1447

Date: 5 / 24 / 04Inspector: SWRound Level: 1201

- ☒ Measure Headspace Min +.002
- ☒ Inspect Take Down Screws for loosening. Front screw 1/4 Turn
- ☐ Sear Engagement: 1st. .0378 2nd. .0378 3rd. .0377 Ave. .03776 spec- .025" to .030"
- ☒ Reset Sear Engagement if Required: 1st. .0312 2nd. .0314 3rd. .0313 Ave. .03130
- ☒ Trigger Pull: 1st. 4.308 2nd. 4.363 3rd. 4.333 Ave. 4.334 spec- 4.5 lb. to 5.5 lb.
- ☒ Reset Trigger Pull if Required: 1st. 5.216 2nd. 5.151 3rd. 5.261 Ave. 5.209
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: Locking lugs normal wear OK
- ☒ Inspect stock for any signs of cracking or other failure: OK
- ☐ Other items of note: _____

TLW1216

Remington Confidential

ET21632