

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum 7mm RM

Project: 241314

Rifle: A-15

TLW #: TLW1447

Date: 5 / 23 / 04Inspector: SWRound Level: 701

- ☒ Measure Headspace Min 4.001
- ☒ Inspect Take Down Screws for loosening. Front screw 1/16 Turn
- ☒ Sear Engagement: 1st. .0360 2nd. .0360 3rd. .0363 Ave. .0361 spec- .025" to .030"
- ☐ Reset Sear Engagement if Required: 1st. 2nd. 3rd. Ave.
- ☒ Trigger Pull: 1st. 4.523 2nd. 4.467 3rd. 4.674 Ave. 4.553 spec- 4.5 lb. to 5.5 lb.
- ☐ Reset Trigger Pull if Required: 1st. 2nd. 3rd. Ave.
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: Locking normal wear, OK
- ☒ Inspect stock for any signs of cracking or other failure: OK
- ☐ Other items of note:

TLW1216

Remington Confidential

ET21642