

GUN# A-16
SERIAL # 71163078
CAL- 7mm REM MAG

REMINGTON M/710 MAGNUM
7MM REM MAG
TRIAL and PILOT # 1
DAILY TEST DATA SHEET

TRACKING # TLW1447
PROJECT #241314

BARBER - 5.22.06r0004643

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-	
				RDS. FIRED	TOTAL RDS.
SW/JS	4/25/04	Head space	Min +.004	TLW1447A	
"	"	Head space	Bolt Type GO won't close	"	
SW/JS	4/25/04	Proof Rd	OK Hammer bolt back	TLW1447B	1
↓	4/26/04	Head space	Min +.004	TLW1447C	
↓	"	Head space	Bolt Type GO won't close	"	
SW	4/26/04	Firing Pin Indent	.017, .017, .017 Avg .0170	TLW1447D	
↓	4/27/04	Check Looseness	Torque front screw 35 in/lbs	TLW1447Z	
↓		Check Depth of	front take down screw hole .0140		
↓		Check number of turns to loosen front screw	1 3/4 Turn		
↓		Inspect trends & measure length	OK / 1.4905		
↓		Engagement	.0340, .0343, .0343 Avg .03420	TLW1447E	
↓		Trigger Pull		TLW1447F	
↓			5.366, 5.352, 5.363, 5.300, 5.360 Avg 5.348	11	
SW	4/28/04	Screw 1st	.0140	TLW1447E	
SW	4/29/04	Torque Front screw	70 in/lbs	TLW1447	
SW	4/30/04	200 Rd Basic Jack Function Test		TLW1447P	200
BL	5-6-04	Clean Bolt & Bore			
PKR	5/11/04	Endurance	100 rds	TLW1447A	100
PKR	5/20/04	Investigate Hard Extract Issue	Shoot additional Rds. of Fed. & Win. Ammo & inspect cases. Case had severe scuffing approx 1/8" ahead of belt. Inspected chamber w/ bore scope small burr/lip raise @ front edge of belt counter bore.		
		Burnished Chamber w/ proper tool received from Ilion & took photos			
		Function Test - Test fire same ammo as used in Jack Function w/ no problems		100	401
SW	5/23/04	Endurance	300 Rds	TLW1447A	300
SW	5/25/04	Clean & Inspect	Head space Min +.005	TLW1447S	701

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

FORMS.XLS

Confidential - Subject - 5.22.06r0004643e Order

ET21643

Williams V. Remington