

## CONFIDENTIAL

Remington Arms Company Inc.  
Research & Development Technical Center  
315 West Ring Road  
Elizabethtown, KY 42701

## Clean &amp; Inspect Checklist

Model: 710 Magnum 7mm RM

Project: 241314

Rifle: A-20

TLW #: TLW1447

Date: 8 / 23 / 04Inspector: SWRound Level: 1201

- ☒ Measure Headspace Min +1.001
- ☒ Inspect Take Down Screws for loosening. Front screw 0 Turn 83
- ☐ Sear Engagement: 1<sup>st</sup> .0362 2<sup>nd</sup> .0361 3<sup>rd</sup> .0363 Ave. .03620 spec- .025" to .030"
- ☐ Reset Sear Engagement if Required: 1<sup>st</sup>      2<sup>nd</sup>      3<sup>rd</sup>      Ave.
- ☒ Trigger Pull: 1<sup>st</sup> 4.513 2<sup>nd</sup> 4.587 3<sup>rd</sup> 4.564 Ave. 4.555 spec- 4.5 lb. to 5.5 lb.
- ☐ Reset Trigger Pull if Required: 1<sup>st</sup>      2<sup>nd</sup>      3<sup>rd</sup>      Ave.
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: Locking lugs normal wear OK
- ☐ Inspect stock for any signs of cracking or other failure.
- ☐ Other items of note:

TLW1216

Remington Confidential

ET21703