

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum 7mm RM

Project: 241314

Rifle: A-21

TLW #: TLW1447

Date: 5 / 19 / 04Inspector: SWRound Level: 701

- ☒ Measure Headspace Min 4.002.
- ☒ Inspect Take Down Screws for loosening. Front Screw 1/2 Turn 83
- ☒ Sear Engagement: 1st .0332 2nd .0331 3rd .0332 Ave. .03316 spec- .025" to .030"
- ☐ Reset Sear Engagement if Required: 1st _____ 2nd _____ 3rd _____ Ave. _____
- ☒ Trigger Pull: 1st 4.282 2nd 4.194 3rd 4.339 Ave. 4.272 spec- 4.5 lb. to 5.5 lb.
- ☒ Reset Trigger Pull if Required: 1st 5.306 2nd 5.331 3rd 5.344 Ave. 5.327
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: OK
- ☒ Inspect stock for any signs of cracking or other failure: OK
- ☐ Other items of note: _____

TLW1216

Remington Confidential

ET21713