**GUN# A-22**
**SERIAL # 71163118**
**CAL- 7mm REM MAG**

# REMINGTON M/710 MAGNUM
## 7MM REM MAG
## TRIAL and PILOT # 1
DAILY TEST DATA SHEET

TRACKING # TLW1447
PROJECT #241314

| NAME | DATE | TEST ACTIVITY | COMMENTS | ROUNDS AT START- | RDS. FIRED | TOTAL RDS. |
|---|---|---|---|---|---|---|
| SW/JS | 4/23/04 | Head space | Min +.001 | TLW1447A | | |
| " | " | Head space | Belt Tyne GO won't close | " | | |
| SW/JS | 4/23/04 | Proof Rd | OK Hammer bolt back | TLW1447B | 1 | 1 |
| | 4/26/04 | Head space | Min +.001 | TLW1447C | | |
| | " | Head space | Belt Tyne GO won't close | " | | |
| SW | 4/26/04 | Firing Pin Indent | .019, .018, .018 Avg .0183 | TLW1447D | | |
| | 4/27/04 | Check Loosening | Torque front screw 37 in lbs | TLW1447Z | | |
| | | Check Depth of front tube down screw hole | .0140 | | | |
| | | Check number of turns to loosen front screw | 2. turns | | | |
| | | Inspect threads + measure length | OK / 1.4380 | | | |
| | | Engagement | .0342, .0343, .0344 Avg .03436 | TLW1447E | | |
| | | Trigger Pull | | TLW1447F | | |
| | | | 4.973, 4.944, 4.985, 4.909, 4.963 Avg 4.955 | " | | |
| SW | 4/28/04 | Sear 1.57 | .0112 | TLW1447E | | |
| SW | 4/29/04 | Torque Front screw | 70 in lbs | TLW1447 | | |
| SW | 5/3/04 | 200 Rd Basic | Jack Function Test | TLW1447P | 200 | 201 |
| BL | 5-6-04 | Clean Bore & Bolt | | | | |
| BL | 5-13-04 | Ext. Function & Endurance Test | 0- Malfunctions | TLW1447R | 500 | 201 |
| SW | 5/19/04 | Clean + Inspect | Head space Min +.001 | TLW1447S | | |

83

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

FORMS.XLS

BARBER - 5.22.06r0004714

Confidential - Subject to Protective Order
Williams v. Remington

ET21714