

TRACKING #TLW1447
PROJECT #241314

NAME	DATE	TEST ACTIVITY	COMMENTS	ROUNDS AT START-	
				RDS. FIRED	TOTAL RDS.
SW/JS	4/26/04	Head space	Min 1.001	TLW1447A	
"	"	Head space	Belt Type GO won't close	"	
SW/JS	4/28/04	Proof Rd	OK	TLW1447B	1
↓	4/26/04	Head space	Min 1.002	TLW1447C	
SW	4/26/04	Head space	Belt Type GO won't close	"	
↓	4/26/04	Firing Pin Indent	.018, .019, .018 Avg .0183	TLW1447D	
↓	4/28/04	Check loosening torque front screw	38 in lbs	TLW1447Z	
↓	↓	Check depth of front takedown screw hole	.0140	↓	
↓	↓	Check number of turns to loosen front screw	2-turns	↓	
↓	↓	Inspect threads & measure length	OK / 14465	↓	
↓	↓	Engagement	.0330, .0319, .0321, Avg .03200	TLW1447E	
↓	↓	Trigger Pull		TLW1447F	
SW	4/28/04	4.690, 4.700, 4.745, 4.730, 4.674, Avg 4.706		"	
SW	4/28/04	Serv lift	.0194	TLW1447E	
SW	4/29/04	Torque front screw	40 in lbs	TLW1447	
SW	8/2/04	200 Rd Basic Jack Function Test		TLW1447P	200
BL	5-6-04	Clean Bore & Bolt			
SW	5/17/04	EX Function & Endurance Test	1-Multifunction	TLW1447R	500
SW	5/19/04	Clean & Inspect	Head space Min 1.002	TLW1447S	701

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

FORMS.XLS

CONFIDENTIAL - SUBPAR 5.2.2.0610004744e Order

ET21744

BARBER - 5.22.06T0004744