

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum 7mm RM

Project: 241314

Rifle: A-75

TLW #: TLW1447

Date: 5 / 19 / 04Inspector: SWRound Level: 701☒ Measure Headspace Min + .002☒ Inspect Take Down Screws for loosening. Front Screw 1/4 Turn☒ Sear Engagement: 1st. .0342 2nd. .0345 3rd. .0344 Ave. .03436 spec- .025" to .030"☐ Reset Sear Engagement if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____☒ Trigger Pull: 1st. 4.629 2nd. 4.834 3rd. 4.707 Ave. 4.723 spec- 4.5 lb. to 5.5 lb.☐ Reset Trigger Pull if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: working lugs little wear. OK☒ Inspect stock for any signs of cracking or other failure: OK☐ Other items ofnote: _____

TLW1216

Remington Confidential

ET21753