

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum 7mm RM

Project: 241314

Rifle: A-27

TLW #: TLW1447

Date: 5 / 19 / 04Inspector: SWRound Level: 701
☒ Measure Headspace Min +.002.

☒ Inspect Take Down Screws for loosening. Front Screw 1/16 Turn
☐ Sear Engagement: 1st. .0367 2nd. .0366 3rd. .0369 Ave. .03673 spec- .025" to .030"

☐ Reset Sear Engagement if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____

☒ Trigger Pull: 1st. 4.434 2nd. 4.369 3rd. 4.415 Ave. 4.406 spec- 4.5 lb. to 5.5 lb.

☒ Reset Trigger Pull if Required: 1st. 5.380 2nd. 5.323 3rd. 5.355 Ave. 5.353
☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: Locking lugs little wear
☒ Inspect stock for any signs of cracking or other failure: OK
☐ Other items of note: _____

TLW1216

Remington Confidential

ET21773