

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum 7mm RM

Project: 241314

Rifle: A-29

TLW #: TLW1447

Date: 5 / 19 / 04Inspector: SVRound Level: 701

- ☒ Measure Headspace Min +.003
- ☒ Inspect Take Down Screws for loosening. Front Screw 1/4 Turn 83
- ☒ Sear Engagement: 1st. .0356 2nd. .0355 3rd. .0357 Ave. .0356 spec- .025" to .030"
- ☐ Reset Sear Engagement if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____
- ☒ Trigger Pull: 1st. 5.020 2nd. 5.002 3rd. 5.015 Ave. 5.032 spec- 4.5 lb. to 5.5 lb.
- ☐ Reset Trigger Pull if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____
- ☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: locking lugs little wear OK
- ☒ Inspect stock for any signs of cracking or other failure: OK
- ☐ Other items of note: _____

TLW1216

Remington Confidential

ET21793