

OPERATIONS COMMITTEE
FIREARMS - TRAPS

MINUTE # 14 - 1982

J.P. McANDREWS
E.F. BARRETT
R.E. FIELITZ
E. HOOTON, JR.
R.W. STEELE
J.G. WILLIAMS
R.A. PARTNOY
E.B. BEATTIE
L. FOX
C.A. RILEY
M.C. ZUMSTEG

H.K. BOYLE
W.H. FORSON, JR.
P.H. HOLMBERG
L.J. SCOTT
R.L. HALL
A.J. HERMANDORFER
W.H. COLEMAN, JR.
C.B. WORKMAN
J.R. AYERS
T.W. RAWSON
G.D. CAMPBELL

COPY NO. _____

OPERATIONS COMMITTEE

ILION DIVISION

JULY 28, 1982

PRESENT:

COMMITTEE:

E.F. BARRETT, CHAIRMAN
R.E. FIELITZ
R.L. HALL
E. HOOTON, JR.
J.G. WILLIAMS
G.D. CAMPBELL, SECRETARY

OTHERS:

J.W. BOWER
H.K. BOYLE
T.L. CAPELETTI
W.W. COOK
W.H. FORSON, JR.
P.H. HOLMBERG
J.P. LINDE
T.W. RAWSON
L.J. SCOTT
R.E. SCHRADER
C.B. WORKMAN

The meeting convened at 8:35 AM.

IREM 00279-1

REMINGTON ARMS COMPANY, INC.

INTER-DEPARTMENTAL CORRESPONDENCE

Remington

478

PETERS

478

Xc: J. W. Brooks
J. S. Martin
F. E. Martin

"CONFINE YOUR LETTER TO ONE SUBJECT ONLY" _____

April 30, 1982

TO: C. B. WORKMAN
FROM: T. L. CAPELETTI *TC*
SUBJECT: BOLT ACTION RIFLE DEVELOPMENT — REPLACEMENT FOR MODEL 700

Based on our discussion Friday, April 23, the proposed specifications for bolt action rifle development are as follows:

A. Preferred DesignB. Contingency Design #1C. Contingency Design #21) Receiver

- | | | |
|-------------------------------------|-------------------------------------|--------------------------------|
| a) Flat bottom octagonal | a) Round bottom octagonal | a) Full round |
| b) Integral recoil lug | b) M/700 - thicker | b) M/700 - thicker |
| c) Integral & standard scope mounts | c) Integral & standard scope mounts | c) Standard scope mounts |
| d) Anti-bind bolt | d) M/700 - no bind | d) M/700 - no bind |
| e) Front lock — two lug system | e) Front lock — two lug system | e) Front lock — two lug system |
| f) Short and long actions | f) Short and long actions | f) Short and long actions |
| g) New bolt stop-release | g) New bolt stop-release | g) M/700 |

A. Preferred DesignB. Contingency Design #1C. Contingency Design #22) Safety

a) Block trigger and firing pin

a) Block trigger and firing pin

a) Block trigger and sear

b) Reposition switch to bolt plug

b) Reposition switch to tang

b) M/700

c) Independent Bolt lock

c) Independent bolt lock

c) No bolt lock

d) Cocking indicator

d) Cocking indicator

d) Cocking indicator

3) Fire Controla) Fully adjustable in stock - With limits on engagement
— Safe lower limita) Weight of pull adjustable in stock
— Pre set engagement and overtravel

a) Tamper proof M/700

b) Standard trigger

b) Standard trigger

b) Double set trigger

c) Exposed components
— No housing

c) Skeletonized housing

c) Skeletonized housing

4) Barrel

a) High gloss without removing hammer marks

a) High gloss without removing hammer marks

a) M/700

b) Light weight contour

b) Light weight contour

b) Light weight contour

c) Target crown

c) Target crown

c) Target crown

d) Recoil reducing muzzle device - Option

d) Recoil reducing muzzle device - Option

d) No recoil reducing device

e) Stainless steel - Option

e) Carbon steel

e) Carbon steel

f) Clean barrel

f) Drilled & tapped for iron sights
— no sights

f) Iron sights