

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum 7mm RM

Project: 241314

Rifle: A-30

TLW #: TLW1447

Date: 5 / 25 / 04Inspector: SWRound Level: 701

- ☒ Measure Headspace Min +.002
- ☒ Inspect Take Down Screws for loosening. Front Screw 3/8 Turn
- ☒ Sear Engagement: 1st. .0374 2nd. .0372 3rd. .0373 Ave. .0372 spec- .025" to .030"
- ☐ Reset Sear Engagement if Required: 1st. 2nd. 3rd. Ave.
- ☒ Trigger Pull: 1st. 4.696 2nd. 4.682 3rd. 4.666 Ave. 4.681 spec- 4.5 lb. to 5.5 lb.
- ☐ Reset Trigger Pull if Required: 1st. 2nd. 3rd. Ave.
- ☒ Inspect cam surface, locking lips and bolt stop for signs of excessive wear: locking lips normal wear, OK
- ☒ Inspect stock for any signs of cracking or other failure: OK
- ☐ Other items of note:

TLW1216

Remington Confidential

ET21803