GUN # A-28
REM MODEL 710
SERIAL # 71203220
7MM REM MAG CAL.

M/710 EXTRUDED RECEIVER TRIAL AND PILOT # 1

TLW 1689
PROJECT # 241314

NAME	DATE	TEST ACTIVITY	COMMENTS		RDS. FIRED	TOTAL RDS.
B.LEE	1-25-05	Initial Headspace	Mint .006	TLW1689B		
B.LEE	1-26-05	PROOF	OK scratches on casing	TLW1689C	1	1
B.LEE	1-26-05	Headspace	Mint .006	TLW1689D		
B.LEE	1-27-05	Firing Pin Indent	.020 - .020 - .021 Avg .0203	TLW1689E		
HJC	1-31-05	Safe On/Off	Data Sheet	TLW1689I		
HJC	2-2-05	Sear Eng / Lift	"	TLW1689F		
B.LEE	2-3-05	Screw Depth	"	TLW1689A		
B.LEE	2-3-05	Trigger Pull	"	TLW1689H		
B.LEE	2-7-05	Firing Pin Head Engagement		TLW1689G		
HJC	2-7-05	Screw De-torque Force	"	TLW1689A		
B.Lee	2-8-05	Torque Screws to Spec	Front 15 in Lb - middle 30-35 in Lb			
			Rear 15 in Lb	TLW1689		
JLW	2-15-05	JACK FUNCTION	200 RDS. COULD NOT OPEN BOLT	TLW1689L	200	201
			AFTER FIRING EACH ROUND - CHAMBER MARKINGS			
			ON BRASS * SAVED SOME BRASS			
SW/JS	2/16/05	Set-up	Set Engagement & Trigger For Jar-Off			
SW/JS	2/17/05	5x2mi Jar-Off	PASS	TLW1689Y		
SW/JS	2/17/05	5x2mi Rotation	PASS	TLW1689Z		
SW/JS	2/18/05	5x2mi Drop	PASS (Cut-ched Insert)	TLW1689AA		
↓	2/22/05	↓	Bottom Down	↓		
↓	"		Replaced Insert			

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

83

FORM DTDS.XLS