GUN # A-36
REM MODEL 710
SERIAL # 71202993
.300 WIN MAG CAL.

M/710 EXTRUDED RECEIVER TRIAL AND PILOT # 1

TLW 1689
PROJECT # 241314

NAME	DATE	TEST ACTIVITY	COMMENTS		RDS. FIRED	TOTAL RDS.
B.LEE	1-25-05	Initial Headspace	Min .003	TLW1689B		
B.LEE	1-26-05	PROOF	OK	TLW1689C	1	1
B.LEE	1-26-05	Headspace	min .003	TLW1689D		
B.LEE	1-27-05	Firing Pin Indent	.019 - .019 - .021 Avg : 0196	TLW1689E		
HJC	1-31-05	Safe On/Off	Data Sheet	TLW1689I		
HJC	2-2-05	Sear Eng-Lift	"	TLW1689F		
B.LEE	2-4-05	Screw Depth	"	TLW1689A		
B.LEE	2-4-05	Trigger Pull	"	TLW1689H		
B.LEE	2-7-05	Firing Pin Head Engagement	"	TLW1689G		
HJC	2-7-05	Screw De-torque Force	"	TLW1689A		
B.LEE	2-8-05	Torque Screws to Spec	Front 75 in Lb - middle 30-35 in Lb			
			Rear 15 in Lb	TLW1689		
B.LEE	2-15-05	200 Rd Jack Function		TLW1689L	200	201
PKR	2/17/05	Cold Test	- Store Gun & Ammo in Freezer			
JLW	2-18-05	COLD FUNCTION TEST		TLW1689T	100	301

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

83

FORM DTDS.XLS

BARBER - 5.22.06r0004954

Confidential - Subject to Protective Order
Williams v. Remington

BARBER - 5.22.06r0004954

ET21954