

C6349212

MODEL 700TM M24

Model **SWS** TM

Action

Barrel Length

Capacity

Order No. **5716**

*Includes 1 in chamber.



Remington
REMINGTON & CO. N.Y. U.S.A. REG. U.S. PAT. & TM. OFF. MARCA REGISTRADA MARQUE DÉPOSÉE.

MODEL 700™ H24

UPPONT
REG. U.S. PAT. & TM. OFF.

VERY IMPORTANT:
Instruction Book
enclosed to assure
safe use of this
firearm.

SERIAL NO.
C6349212

ORDER NO.
5716

Ø1

MADE IN ILION, N.Y. U.S.A. Reg. U.S. Pat. & Tm. Off. Marca Registrada Marque Deposee.

5716 C6349212

UPC

0 47700 25716 7

GUN SERIAL # C6349212

OP. #	OP. NAME	READINGS	DATE	INIT
575 & 580	Assemble Action and Stock	1 12	90	RW
600	Proof	1 12	90	L
607	Check Headspace	1 12	90	L
610	Dis-assemble Gun	1 12	90	RW
612	Magnaflux Barrel Action	1-16-90		KCR
	Magnaflux Bolt	1-17-90		KCR
615	Rollmark Caliber	1-17-90		ES
617	Drill and Tap Sight Holes	1-19-90		FB
618	Polish Barrel RB	22 1-22-90		WB
620	Apply Coatings (Barrel Action)		20-90	DA
	Apply Coating (Bolt)			
625	Final Assembly		2/2/90	WB
	A) Clean inside of Bolt Assembly			
	B) Inspect Rear Firing Pin Hole for Chamfer in Bolt Head			
	C) Inspect Ejector Hole for Chamfer			
	D) Oil Firing Pin Ass'y			
	E) Adjust Trigger Pull to Min Setting and Stake		3/1/90	DS

op. #	BARBER REM24 0110279	READINGS					DATE	INIT
625 cont.	F) Safety On Force	5	5	5			1-31-90	GU
	G) Safety Off Force	3	3	3			1-31-90	GU
	H) Trigger Pull Test & Retainability						31/1/90	GU
	I) Firing Pin Indent	.023	.023	.023			1-31-90	GU
	J) Assemble Stock						1-31-90	K
	K) Assemble Swivel Studs						1/28/90	WB
	L) Attach Front and Rear Sight Assemblies						1-31-90	K
	M) Iron Sight Alignment						1-31-90	K
	N) Detach Front & Rear Sights & place in numbered container						1-31-90	K
	O) Attach Scope to Rifle						2-23-90	GU
	P) Detach & Attach Scope 20 Times						2-23-90	GU
640	Gallery Target & Test						2-26-90	K
	A) Time						"	K
	B) Malfunctions						"	K
	C) Pierced Primers						"	K
	D) Optical Clarity of Scope						"	K
645	Inspect for Live Ammo						2-26-90	K
655	Final Inspection						1/28/90	WB
	A) Headspace						1/27/90	WB
	B) Trigger Pull	2.78	2.77	2.78	2.78	2.78	1/27/90	WB
	C) Function						1/28/90	WB
660	Pack						20/1/90	GU

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# ± .50#

3.00# ± .75#

4.00# ± 1.00#

SERIAL NO. C6349212

DATE 31 Jan 90

TESTER hss

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#		COMMENTS
PULL #1	251	268	239	278	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	255	260	230	277	
PULL #3	253	257	233	278	
PULL #4	245	258	231	278	
PULL #5	251	253	234	278	
TOTAL	1255	1293	1167		
AVG.	2.51	2.586	2.334		

	3.00# INITIAL	3.00# AFTER 20 CYCLES		COMMENTS
PULL #1	279	299		
PULL #2	306	272		
PULL #3	306	267		
PULL #4	306	290		
PULL #5	282	292		
TOTAL	1479	1420		
AVG.	2.958	2.84		

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	396	404		4.05
PULL #2	395	364		3.91
PULL #3	386	372		3.84
PULL #4	394	393		3.77
PULL #5	391	379		3.86
TOTAL	1962	1912		1948
AVG.	3.924	3.824		3.896


CENTROIDAL DISTANCE CALCULATIONS
FOR RIFLE # 06349212
26 Feb 1990

CENTROIDAL DISTANCES

0	TO	1	.215058
1	TO	2	.481627
1	TO	3	.201457
1	TO	4	.0845044
1	TO	5	.437696

5 <----POB

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: -.0728
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: .0054
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: .073
THE AMR FOR THIS RIFLE IS: .8554




PATTERN #	1	2	3
SHOTS (BEST OF)	10	9	8
MAXIMUM X	.975	1.055	1.038
MINIMUM X	-.978	-.898	-.766
MAXIMUM Y	1.129	.995	.897
MINIMUM Y	-1.214	-.843	-.941
CENTROID X	-.125	-.205	-.337
CENTROID Y	.175	.318	.488
POB TO CENTROID in.	.216	.372	.529
MIN RADIUS	.661	.646	.490
MEAN RADIUS	.959	.890	.812
MAX RADIUS	1.412	1.313	1.042
HORIZONTAL SPREAD	1.953	1.953	1.796
VERTICAL SPREAD	2.343	1.838	1.838
EXTREME SPREAD	2.389	2.058	1.673
NUMBER IN ONE INCH CIRCLE =	0		
NUMBER IN TWO INCH CIRCLE =	7		
NUMBER IN THREE INCH CIRCLE =	10		

01/01/1998

FILE:/PATTERNING/CENTERFIRE_PATT/06345212

CENTERFIRE PATTERNS

2



OF SHOTS = 10

IN CIR

1 in = 1

2 in = 8

3 in = 10

HS = 1.774

VS = 1.734


GS = 1.881

PATTERN #	1	2	3
SHOTS (BEST OF)	10	9	8
MAXIMUM X	.800	.692	.719
MINIMUM X	-.974	-.621	-.535
MAXIMUM Y	.856	.899	.983
MINIMUM Y	-.878	-.835	-.751
CENTROID X	-.274	-.166	-.252
CENTROID Y	-.283	-.326	-.410
FOR TO CENTROID in.	.394	.366	.482
MIN RADIUS	.437	.481	.467
MEAN RADIUS	.836	.804	.773
MAX RADIUS	1.048	1.000	1.038
HORIZONTAL SPREAD	1.774	1.313	1.254
VERTICAL SPREAD	1.734	1.734	1.734
EXTREME SPREAD	1.881	1.881	1.877
NUMBER IN ONE INCH CIRCLE =		1	
NUMBER IN TWO INCH CIRCLE =		8	
NUMBER IN THREE INCH CIRCLE =		10	

13 Feb 1990

FILE:/PATTERNING/CENTERFIRE_PATT/08349212

CENTERFIRE PATTERNS # 3



OF SHOTS- 10

IN CIR

1in = 1

2in = 8

3in = 10

HS= 1.621

VS= 1.876

GS= 1.983

CENTROID *


PATTERN #	3
SHOTS (BEST OF)	10
MAXIMUM X	.792
MINIMUM X	-.829
MAXIMUM Y	.904
MINIMUM Y	-.972
CENTROID X	-.186
CENTROID Y	-.017
POA TO CENTROID in.	.187
MIN RADIUS	.435
MEAN RADIUS	.755
MAX RADIUS	1.227
HORIZONTAL SPREAD	1.621
VERTICAL SPREAD	1.876
EXTREME SPREAD	1.983
NUMBER IN ONE INCH CIRCLE	1
NUMBER IN TWO INCH CIRCLE	8
NUMBER IN THREE INCH CIRCLE	10

20 Feb 1988

FILE:/PATTERNING/CENTERFIRE_PATT/C8348212

CENTERFIRE PATTERNS

4



OF SHOTS = 10

IN CIR

1in = 2

2in = 6

3in = 10

HS = 2.000

VS = 2.023

CS = 2.211


CENTROID *

PATTERN #	4		
SHOTS (BEST OF)	10	9	8
MAXIMUM X	.999	.988	1.087
MINIMUM X	-1.099	-1.110	-1.011
MAXIMUM Y	.798	.662	.705
MINIMUM Y	-1.225	-1.400	-1.317
CENTROID X	-.071	-.060	-.159
CENTROID Y	.110	.246	.163
POA TO CENTROID in.	.130	.253	.228
MIN RADIUS	.250	.277	.160
MEAN RADIUS	.811	.767	.707
MAX RADIUS	1.228	1.134	1.099
HORIZONTAL SPREAD	2.098	2.098	2.098
VERTICAL SPREAD	2.023	1.062	1.022
EXTREME SPREAD	2.211	2.098	2.098
NUMBER IN ONE INCH CIRCLE =		2	
NUMBER IN TWO INCH CIRCLE =		6	
NUMBER IN THREE INCH CIRCLE =		10	

26 Feb 1998

FILE:/PATTERNING/CENTERFIRE_PATT/C8348212

CENTERFIRE PATTERNS # 5



OF SHOTS- 10

IN CIR

1 in = 3

2 in = 5

3 in = 9

HS= 3.013

VS= 2.063

GS= 3.076

PATTERN #	5	5	5
SHOTS (BEST OF)	10	9	8
MAXIMUM X	1.363	1.189	1.101
MINIMUM X	-1.653	-1.928	-1.781
MAXIMUM Y	.979	1.006	1.067
MINIMUM Y	-1.084	-1.037	-1.056
CENTROID X	.292	.475	.323
CENTROID Y	.042	-.005	.014
POA TO CENTROID in.	.295	.475	.323
MIN RADIUS	.277	.100	.232
MEAN RADIUS	.916	.816	.759
MAX RADIUS	1.703	1.189	1.249
HORIZONTAL SPREAD	3.013	2.108	1.862
VERTICAL SPREAD	2.063	2.063	2.063
EXTREME SPREAD	3.076	2.199	2.153
NUMBER IN ONE INCH CIRCLE =		3	
NUMBER IN TWO INCH CIRCLE =		5	
NUMBER IN THREE INCH CIRCLE =		9	