EXHIBIT 34

MODEL 700™ M24

BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

DOCUMENT ENVELOPE ASSEMBLY:
- INSTUCTION BOOK
- PRODUCT OWNER'S CARD
- SAFETY BOOKLET

46 FORM 1444




VERY IMPORTANT
Instruction Book
enclosed to assure
safe use of this
firearm.
Remington®
MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
Made in Ilion, NY. Reg. U.S. Pat. & Tm. Off. Marca Registrada Marque Deposee.
SERIAL NO. J E6790524
ORDER NO. 46 25716
22BW
5716 E6790524

ORDER 25716
MODEL 700™ M24
UPC
0 47700 25716 7
ORDER 25716
MODEL 700™ M24
UPC
0 47700 25716 7
SERIAL NO.
E6790524

M-24

6 5

CONTRACT #

GUN SERIAL # FL079052Y

OP #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK		11-30-01	KAL
600	PROOF		11-30-01	KAL
607	CHECK HEADSPACE		11-30-01	KAL
610	DIS-ASSEMBLE GUN		11-30-01	KAL
612	MAGNAFLUX BBL ACTION MAGNAFLUX BOLT		DEC 5 2001 OPERATOR	
615	ROLLMARK CALIBER		12/5/01	SB
617	DRILL AND TAP SIGHT HOLES		12/6/01	BWT
620	APPLY COATINGS (BARREL ACTION)		12/	
	(BOLT)			
625	FINAL ASSEMBLY A) CLEAN INSIDE OF BOLT ASSEMBLY		1/14/02	D.M.
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		1/14/02	D.M.
	C) INSPECT EJECTOR HOLE FOR CHAMFER		1/14/02	D.M.
	D) OIL FIRING PIN ASSEMBLY		1/14/02	D.M.
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS		1-22-02	DM

OP #	OPERATION NAME	READINGS	DATE	INITIAL
625	F) SAFETY ON FORCE (2 LBS MIN / 10 LBS MAX)	5.25 5.25 6.25	1/21/02	D.M.
CONT.	G) SAFETY OFF FORCE (2 LBS MIN)	3.25 4.00 3.50	1/21/02	D.M.
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT (.020 MIN)	.023 .025 .022	1/21/02	D.M.
	J) ASSEMBLE STOCK		1-18-02	RH
	K) ASSEMBLE SWIVEL STUDS		1/9/02	Kw
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640	GALLERY TEST AND TARGET	PASS FAIL	1-18-02	A
	A) MALFUNCTIONS	PASS FAIL	1-18-02	A
	B) PIERCED PRIMERS	PASS FAIL	1-18-02	A
645	INSPECT FOR LIVE AMMO		1-18-02	A
655	FINAL INSPECTION A) HEADSPACE		1/9/02	Kw
	B) TRIGGER PULL (+/- .5 LBS, MIN 2.50 LBS, MAX 4.0 LBS)	2.07 2.15 3.96 2.20 2.15	1/21/02	D.M.
	C) FUNCTION		1/21/02	Kw
660	PACK		1-22-02	DA

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS
2.50# ± .50#
3.00# ± .75#
4.00# ± 1.00#

SERIAL NO. E67905 24
DATE 1/16/02
TESTER D.M.

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#		COMMENTS
PULL #1	2.76	2.31		2.67	MIN. SETTING,
PULL #2	2.68	2.54		2.63	NO AVG. OF 5
PULL #3	2.62	2.54		2.58	READINGS ACCEPT-
PULL #4	2.43	2.61		2.64	ABLE LESS THAN 2#
PULL #5	2.46	2.43		2.83	
TOTAL	12.95	12.43		13.35	
AVG.	2.59	2.49		2.67	

	3.00# INITIAL	3.00# AFTER 20 CYCLES		COMMENTS
PULL #1	3.33	3.27		
PULL #2	3.42	3.55		
PULL #3	3.44	3.49		
PULL #4	3.27	3.48		
PULL #5	3.42	3.51		
TOTAL	16.88	17.30		
AVG.	3.38	3.46		

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.27	4.36		4.26
PULL #2	4.16	4.30		4.23
PULL #3	4.11	4.33		4.12
PULL #4	4.17	4.19		4.19
PULL #5	4.40	4.23		4.16
TOTAL	21.11	21.41		20.96
AVG.	4.22	4.28		4.19

SERIAL NUMBER: E6790524.__0
TARGET NUMBER: 1
FILE DATE: 01/19/2002
FILE TIME: 03:00

X CENTROID:	0.053
Y CENTROID:	0.202
POA TO CENTROID:	0.209
HORZ SPREAD:	1.546
VERT SPREAD:	1.496
GROUP SPREAD:	1.850
MIN RADIUS:	0.408
MAX RADIUS:	1.150
MEAN RADIUS:	0.741
# IN 1 IN DIAMETER:	1
# IN 2 IN DIAMETER:	4
# in 3 IN DIAMETER:	5

POINT#	X	Y
1:	-0.852	-0.507
2:	-0.282	-0.030
3:	0.694	-0.112
4:	0.467	0.672
5:	0.237	0.989



TARGET APPROX 1/2 SCALE

SERIAL NUMBER: E6790524.__0
TARGET NUMBER: 2
FILE DATE: 01/19/2002
FILE TIME: 03:00

X CENTROID:	0.141
Y CENTROID:	-0.041
POA TO CENTROID:	0.147
HORZ SPREAD:	1.834
VERT SPREAD:	1.804
GROUP SPREAD:	2.193
MIN RADIUS:	0.562
MAX RADIUS:	1.439
MEAN RADIUS:	0.878
# IN 1 IN DIAMETER:	0
# IN 2 IN DIAMETER:	4
# in 3 IN DIAMETER:	5

POINT#	X	Y
1:	-0.972	-0.953
2:	-0.107	-0.545
3:	0.862	0.106
4:	0.801	0.337
5:	0.123	0.851



TARGET APPROX 1/2 SCALE