

E6970647

Remington®

**MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO**

Made in Ilion, NY Reg. U.S. Pat. & tm. Off. Marca Registrada Marque Deposee




5716 E6790647

ORDER

25716

MODEL 700™ M24

UPC




0 47700 25716 7

ORDER

25716

MODEL 700™ M24

UPC



0 47700 25716 7

SERIAL NO.




E6790647

MODEL 700TH M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO

DOCUMENT ENVELOPE ASSEMBLY:

- INSTRUCTION BOOK
- PRODUCT OWNER'S CARD
- SAFETY BOOKLET

46 FORM 1444




ORDER NO. 25716

BARREL LENGTH 24"

CAPACITY 6

E6790647



CONTRACT #

GUN SERIAL #

OP #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK		11-9-01	REP
600	PROOF		11-9-01	REP
607	CHECK HEADSPACE		11-9-01	REP
610	DIS-ASSEMBLE GUN		11-9-01	REP
612	MAGNAFLUX BBL ACTION MAGNAFLUX BOLT			AL
615	ROLLMARK CALIBER			
617	DRILL AND TAP SIGHT HOLES		11-9	WM
620	APPLY COATINGS (BARREL ACTION)		11-30 11/29	TA HP
	(BOLT)			
625	FINAL ASSEMBLY			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		12-18	Doog
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		12-18	Doog
	C) INSPECT EJECTOR HOLE FOR CHAMFER		12-18	Doog
	D) OIL FIRING PIN ASSEMBLY		12-18	Doog
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS	1-22-02	JA

OP #	OPERATION NAME		READINGS	DATE	INITIAL
625	F) SAFETY ON FORCE	2 LBS MIN 10 LBS MAX	<u>9</u> <u>7</u> <u>6</u>	1-25-02	RW
CONT.					
	G) SAFETY OFF FORCE	2 LBS MIN	<u>4.5</u> <u>3.5</u> <u>3.5</u>	1-25-02	RW
	H) TRIGGER PULL TEST AND RETAINABILITY				
	I) FIRING PIN INDENT	.020 MIN	<u>1.023</u> <u>1.023</u> <u>1.023</u>	1-25-02	RW
	J) ASSEMBLE STOCK			1-21-02	RH
	K) ASSEMBLE SWIVEL STUDS			1-25-02	RW
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			1-28-02	RA
	M) IRON SIGHT ALIGNMENT			1-28-02	RA
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			1-28-02	RA
640	GALLERY TEST AND TARGET		PASS FAIL	1-22-02	A
	A) MALFUNCTIONS		PASS FAIL	1-22-02	A
	B) PIERCED PRIMERS		PASS FAIL	1-22-02	A
645	INSPECT FOR LIVE AMMO			1-22-02	A
655	FINAL INSPECTION A) HEADSPACE			1-25-02	RW
	B) TRIGGER PULL	+/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.15</u> <u>2.68</u> <u>2.35</u> <u>2.98</u> <u>2.36</u>	1-25-02	RW
	C) FUNCTION			1-25-02	RW
660	PACK			1-28-02	RA

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# + .50#
3.00# + .75#
4.00# + 1.00#

SERIAL NO. E6290647DATE 12/31/01TESTER B.N.

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#	COMMENTS
PULL #1	2.52	2.59	2.50	MIN. SETTING,
PULL #2	2.43	2.40	2.14	NO AVG. OF 5
PULL #3	2.36	2.36	2.71	READINGS ACCEPT-
PULL #4	2.30	2.58	2.50	ABLE LESS THAN 2#
PULL #5	2.24	2.69	2.51	
TOTAL	11.85	12.62	12.36	
AVG.	2.37	2.52	2.47	


	3.00# INITIAL	3.00# AFTER 20 CYCLES	COMMENTS
PULL #1	3.22	3.24	
PULL #2	3.27	3.20	
PULL #3	3.23	3.17	
PULL #4	3.26	3.19	
PULL #5	3.26	3.23	
TOTAL	16.24	16.03	
AVG.	3.25	3.21	

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.13	4.38		4.32
PULL #2	4.18	4.31		4.36
PULL #3	4.67	4.32		4.50
PULL #4	4.55	4.17		3.99
PULL #5	4.59	4.09		
TOTAL	22.12	21.27		21.62
AVG.	4.42	4.25		4.32

SERIAL NUMBER: E6790647. __0
 TARGET NUMBER: 1
 FILE DATE: 01/22/2002
 FILE TIME: 02:30

POINT#	X	Y
1:	-0.104	1.191
2:	-0.792	0.362
3:	0.494	0.289
4:	0.490	-0.044
5:	0.223	-0.455

X CENTROID: 0.062
 Y CENTROID: 0.269
 POA TO CENTROID: 0.276
 HORZ SPREAD: 1.286
 VERT SPREAD: 1.646
 GROUP SPREAD: 1.678
 MIN RADIUS: 0.432
 MAX RADIUS: 0.937
 MEAN RADIUS: 0.700
 # IN 1 IN DIAMETER: 1
 # IN 2 IN DIAMETER: 5
 # in 3 IN DIAMETER: 5




TARGET APPROX 1/2 SCALE

SERIAL NUMBER: E6790647. __0
 TARGET NUMBER: 2
 FILE DATE: 01/22/2002
 FILE TIME: 02:30

POINT#	X	Y
1:	0.384	2.219
2:	0.513	-0.598
3:	-0.282	-0.262
4:	-0.252	0.189
5:	-0.259	0.500

X CENTROID: 0.021
 Y CENTROID: 0.410
 POA TO CENTROID: 0.410
 HORZ SPREAD: 0.795
 VERT SPREAD: 2.817
 GROUP SPREAD: 2.820
 MIN RADIUS: 0.294
 MAX RADIUS: 1.845
 MEAN RADIUS: 0.870
 # IN 1 IN DIAMETER: 2
 # IN 2 IN DIAMETER: 3
 # in 3 IN DIAMETER: 4



TARGET APPROX 1/2 SCALE