CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Extruded Receiver "Std. Caliber"

Project: 241314 **TLW #:** TLW1689

Date: 3 / 1 / 05

Gun Test # A-11 **S/N** 71202772

Round Level: 1711 **Inspector:** B. LEE

83

☑ **Measure Headspace** min+.001.

☑ **Check Takedown Screw Torque @ Disassembly: Frt** 45, **Center** 35, **Rear** 15

☑ **Sear Engagement:** 1st. .0244 2nd. .0250 3rd. .0252 **Ave.** .0248 **spec-** .020" to.025"

☐ **Reset Sear Engagement if Required:** 1st. 2nd. 3rd. **Ave.**

☑ **Trigger Pull:** 1st. 5.921 2nd. 5.918 3rd. 5.831 **Ave.** 5.890 **spec-** 4 lb. to 5.5 lb.

☑ **Reset Trigger Pull if Required:** 1st. 4.849 2nd. 4.868 3rd. 4.991 **Ave.** 4.901

☑ **Inspect Firecontrol Insert for any signs of cracking or other failure.** OK

☐ **Other items of note:**

☑ **Torque Takedown Screws @ Reassembly: SPEC- Frt- 50 in lbs, Center- 30-35 in lbs, Rear- 15 in lbs.**

TLW1216

Remington Confidential

CONFIDENTIAL

ET22063