GUN # A-15
REM MODEL 710
SERIAL # 71202783
270 CAL.

M/710 EXTRUDED RECEIVER TRIAL AND PILOT # 1

TLW 1689
PROJECT # 241314

| NAME | DATE | TEST ACTIVITY | COMMENTS | | RDS. FIRED | TOTAL RDS. |
|---|---|---|---|---|---|---|
| B.LEE | 1-25-05 | Initial Headspace | min .003 | TLW1689B | | |
| B.LEE | 1-25-05 | Proof | OK | TLW1689C | 1 | 1 |
| B.LEE | 1-25-05 | Headspace | min .004 | TLW1689D | | |
| B.LEE | 1-26-05 | Firing Pin Indent | .020 - .020 - .021 Avg .0203 | TLW1689E | | |
| B.LEE | 1-28-05 | Safe on off Force | See data sheet | TLW1689I | | |
| HJC | 2-1-05 | Weight | " " " | TLW1689H | | |
| B.LEE | 2-2-05 | Sear Eng / Lift | " " " | TLW1689F | | |
| B.LEE | 2-3-05 | Screw Depth | " " " | TLW1689A | | |
| B.LEE | 2-3-05 | Trigger Pull | " " " | TLW1689H | | |
| B.LEE | 2-7-05 | Firing Pin Head Engagement | " " | TLW1689G | | |
| HJC | 2-7-05 | Screw De-torque Forces | " " | TLW1689A | | |
| B.LEE | 2-8-05 | Torque Screws to Specification | Front 30 in Lb - Middle 30-35 in Lb | | | |
| | | | Rear 15 in Lb | TLW1689 | | |
| B.LEE | 2-10-05 | 200 rd Tact Function | 11 Bolt Bind on Cue Rd | TLW1689L | 200 | 201 |
| J. Carson | 2/17/05 | 0 - 500 rd | Endurance | TLW1689L | 500 | 701 |
| B.LEE | 2-22-05 | Clean / Inspection | | TLW1689R | | |
| B.LEE | 2-24-05 | Shoulder function | See Data Sheet | TLW1689m | 10 | 711 |

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

83

FORM DTDS.XLS

BARBER - 5.22.06r0005114

Confidential - Subject to Protective Order
Williams v. Remington

ET22114