GUN # A-18
REM MODEL 710
SERIAL # 71202784
270 CAL.

M/710 EXTRUDED RECEIVER TRIAL AND PILOT # 1

TLW 1689
PROJECT # 241314

NAME	DATE	TEST ACTIVITY	COMMENTS	RDS. FIRED	TOTAL RDS.
B.LEE	1-25-05	Initial Headspace	min .002 TLW 1689 B		
B.LEE	1-25-05	Proof	OK TLW 1689 C	1	1
B.LEE	1-25-05	Headspace	min .002 TLW 1689 D		
B.LEE	1-26-05	Firing Pin Indent	.021 - .021 - .021 Avg .021 TLW 1689 E		
B.LEE	1-28-05	Safe on/off Force	See data sheet TLW 1689 I		
B.LEE	2-2-05	Sear Eng/Lift	" " " TLW 1689 F		
B.LEE	2-3-05	Screw Depth	" " " TLW 1689 A		
B.LEE	2-3-05	Trigger Pull	" " TLW 1689 H		
B.LEE	2-7-05	Firing Pin Head Engagement	" " TLW 1689 G		
HJC	2-7-05	Screw De-torque Forces	" " TLW 1689 J		
B.Lee	2-8-05	Torque Screws to Specification	Front 50 in Lb - middle 30-35 IN Lb		
			Rear 15 IN Lb TLW 1689		
B.Lee	2-10-05	Round Feed Function	6 Rdt Rnds on Live Rd - System Low TLW 1689 L	200	201
SW/JS	2/11/05	Set-up	Set Engagement & Trigger Pull Jan-OFF		
SW/JS	2/14/05	Summer Jan-OFF	PASS TLW 1689 Y		
SW/JS	2/14/05	Summer Rotation	PASS TLW 1689 Z		
SW/JS	2/15/05	Summer Drop	PASS TLW 1689 AA		

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

83

FORM DTDS.XLS

BARBER - 5.22.06r0005138

Confidential - Subject to Protective Order
Williams v. Remington

ET22138