

UPC



E6349942

ORDER NO. 25705

BARREL LENGTH 24"

CAPACITY * 6

* INCLUDES 1 IN CHAMBER

BARBER - M24 0123993

Remington Test Lab, Ilion, N.Y.

Centroidal distance calculations for Rifle # E6349942
21 Aug 1997

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: -.022

THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: -.100667

THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: .103043

THE AMR FOR THIS RIFLE IS: 1.1

CENTROIDAL DISTANCES

Ø TO 1 .135831
1 TO 2 .26162
1 TO 3 .180569

2₊
1
3 <----POA

BARBER - M24 0123994


REMINGTON CENTERFIRE ACCURACY TEST

REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: 1
POA TO CENTROID: .136
MIN RADIUS : .461
MEAN RADIUS : 1.167
MAX RADIUS : 1.472
CENTROID X : .069
CENTROID Y : -.117

21 Aug 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6349942

CENTERFIRE PATTERN # 1

OF SHOTS= 5

IN CIRCLE

HS= 2.34

1

VS= 2.26

1

GS= 2.90

5

BARBER - M24 0123995


REMINGTON CENTERFIRE ACCURACY TEST

REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: 2
POA TO CENTROID: .130
MIN RADIUS : .531
MEAN RADIUS : 1.138
MAX RADIUS : 1.885
CENTROID X : -.102
CENTROID Y : .081

21 Aug 1997

FILE:/Hqbasic/Accuracy/Patterning/Centerfire_Patt/E6349942

CENTERFIRE PATTERN # 2

OF SHOTS= 5

IN CIRCLE

HS= 3.06

0

VS= 2.04

3

GS= 3.49

3

BARBER - M24 0123996

REMINGTON CENTERFIRE ACCURACY TEST


REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: 3
 POA TO CENTROID: .268
 MIN RADIUS : .222
 MEAN RADIUS : .996
 MAX RADIUS : 1.747
 CENTROID X : -.033
 CENTROID Y : -.266

21 Aug 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/EG349942

CENTERFIRE PATTERN # 3



OF SHOTS= 5

IN CIRCLE

HS= 1.48
 VS= 2.94
 GS= 2.95

1
 2
 4

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# ± .50#
3.00# ± .75#
4.00# ± 1.00#

SERIAL NO. E6349942DATE 7-29-97TESTER T.M.

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#	COMMENTS
PULL #1	2.43	2.48	2.56	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.41	2.45	2.35	
PULL #3	2.41	2.43	2.53	
PULL #4	2.43	2.44	2.45	
PULL #5	2.41	2.40	2.56	
TOTAL	12.09	12.20	12.45	
AVG.	2.418	2.440	2.490	

	3.00# INITIAL	3.00# AFTER 20 CYCLES	COMMENTS
PULL #1	3.11	3.08	
PULL #2	2.91	3.13	
PULL #3	3.09	3.13	
PULL #4	3.06	3.05	
PULL #5	3.16	3.10	
TOTAL	15.33	15.49	
AVG.	3.066	3.098	

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.18	4.14		4.11
PULL #2	4.16	4.16		3.96
PULL #3	3.90	3.97		3.93
PULL #4	4.15	4.09		4.07
PULL #5	4.14	4.18		3.99
TOTAL	20.53	20.54		20.06
AVG.	4.106	4.108		4.012

ISRAELI GUNS

CONTRACT # DAAE20-97-C-0182

GUN SERIAL # F6349942

OP. #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK			
600	PROOF			
607	CHECK HEADSPACE			
610	DIS-ASSEMBLE GUN			
612	MAGNAFLUX BARREL ACTION			
	MAGNAFLUX BOLT			
615	ROLLMARK CALIBER			
617	DRILL AND TAP SIGHT HOLES			
618	POLISH BARREL			
620	APPLY COATINGS (BARREL ACTION)			
	(BOLT)			
625	FINAL ASSEMBLY A) CLEAN INSIDE OF BOLT ASSEMBLY			
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD			
	C) INSPECT EJECTOR HOLE FOR CHAMFER			
	D) OIL FIRING PIN ASSEMBLY			
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE			


OP. #	OPERATION NAME	READINGS	DATE	INITIAL
625	F) SAFETY ON FORCE	<u>5</u> <u>5</u> <u>5</u>	8-6-97	AC
CONT.	G) SAFETY OFF FORCE	<u>3</u> <u>3</u> <u>4</u>	8-6-97	AC
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT	<u>.023</u> <u>.023</u> <u>.021</u>	8-6-97	AC
	J) ASSEMBLE STOCK		7-31-97	CK
	K) ASSEMBLE SWIVEL STUDS		8-27-97	RP
	L) ATTACH FRONT AND REAR SIGHT ASSY'S		7-31-97	CK
	M) IRON SIGHT ALIGNMENT		7-31-97	CK
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER		7-31-97	CK
640	GALLERY TEST AND TARGET	WIN: <u>L 25</u> <u>R 25</u>	8-21-97	TM
	A) MALFUNCTIONS		8-21-97	TM
	B) PIERCED PRIMERS		8-21-97	TM
645	INSPECT FOR LIVE AMMO		8-21-97	TRD
655	FINAL INSPECTION A) HEADSPACE		8-27-97	RP
	B) TRIGGER PULL	<u>2.71</u> <u>2.76</u> <u>2.75</u> <u>2.77</u> <u>2.70</u>	8-24-97	TM
	C) FUNCTION		8-27-97	RP
660	PACK			

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

GREEN ENVELOPE CONTAINING:

- INSTRUCTION BOOK
- PRODUCT OWNER'S CARD
- MUSEUM/COUNTRY STORE FLIER
- REMINGTON AUTHORIZED GUNSMITHS

46 FORM



Do Not Use

VERY IMPORTANT
Instruction - Book
enclosed to assure
safe use of this
weapon.

Remington®

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

Reg. U.S. Pat. & Tm. Off. Mark Registered Marque Deposited

SERIAL NO
E6349942

46
ORDER NO
25705

08DR

5705 E6349942

ORDER 25705

MODEL 700™ M24

UPC



ORDER 25705

MODEL 700™ M24

UPC



SERIAL NO



E6349942