

BARBER - M24 0124242

UPC



E6349963

CONFIDENTIAL-SUBJECT TO PROTECTIVE ORDER
KINZER V. REMINGTON

BARBER - M24 0124242 M2400124281

ORDER NO. 25705
BARREL LENGTH 24"
CAPACITY * 6

BARBER - M24 0124244

Remington Test Lab, Ilion, N.Y.

Centroidal distance calculations for Rifle # E6349963
4 Sep 1997

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: .273
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: .131
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: .302804

THE AMR FOR THIS RIFLE IS: 1.094

CENTROIDAL DISTANCES

Ø TO 1 .418084
1 TO 2 .754179
1 TO 3 .447189

2
3
+ <----POA
1

BARBER - M24 0124245


REMINGTON CENTERFIRE ACCURACY TEST

REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: 1
POA TO CENTROID: .418
MIN RADIUS : .468
MEAN RADIUS : .956
MAX RADIUS : 1.602
CENTROID X : .325
CENTROID Y : -.263

4 Sep 1997

FILE:/Hqbasic/Accuracy/Patterning/Centerfire_Patt/E6349963

CENTERFIRE PATTERN # 1

OF SHOTS= 5

IN CIRCLE

HS= 1.39

1

VS= 2.56

3

GS= 2.86

4

BARBER - M24 0124246

REMINGTON CENTERFIRE ACCURACY TEST


REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: 2
 POA TO CENTROID: .499
 MIN RADIUS : .766
 MEAN RADIUS : 1.165
 MAX RADIUS : 1.721
 CENTROID X : .159
 CENTROID Y : .472

4 Sep 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6349963

CENTERFIRE PATTERN # 2



OF SHOTS= 5

IN CIRCLE

HS= .68
 VS= 3.02
 GS= 3.05

0
 2
 4

BARBER - M24 0124247


REMINGTON CENTERFIRE ACCURACY TEST

REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: 3
POA TO CENTROID: .385
MIN RADIUS : .765
MEAN RADIUS : 1.160
MAX RADIUS : 1.831
CENTROID X : .338
CENTROID Y : .184

4 Sep 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6349963

CENTERFIRE PATTERN # 3

OF SHOTS= 5

IN CIRCLE

HS= 2.86

0

VS= 1.93

2

GS= 3.01

4

BARBER - M24 0124248

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# + .50#

3.00# + .75#

4.00# + 1.00#

SERIAL NO. E6349963DATE 8-7-97TESTER TM

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#	COMMENTS
PULL #1	2.56	2.40	2.49	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.57	2.62	2.47	
PULL #3	2.57	2.49	2.45	
PULL #4	2.60	2.66	2.46	
PULL #5	2.59	2.60	2.44	
TOTAL	12.89	12.77	12.31	
AVG.	2.578	2.554	2.462	

	3.00# INITIAL	3.00# AFTER 20 CYCLES		COMMENTS
PULL #1	3.20	3.20		
PULL #2	3.18	3.27		
PULL #3	3.25	3.21		
PULL #4	3.20	3.28		
PULL #5	3.29	3.31		
TOTAL	16.12	16.27		
AVG.	3.224	3.254		

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.04	4.14		4.19
PULL #2	4.07	4.09		3.98
PULL #3	4.10	4.16		4.22
PULL #4	4.06	4.09		4.19
PULL #5	4.13	4.18		4.13
TOTAL	20.40	20.66		20.71
AVG.	4.080	4.132		4.142

ISRAELI GUNS

IS-B-YLS

GUN SERIAL # E6349963

OP. #	OP. NAME	READINGS	DATE	INITIAL
575 & 580	Assemble Action and Stock			
600	Proof			
607	Check Headspace			
610	Dis-assemble Gun			
612	Magnaflux Barrel Action			
	Magnaflux Bolt			
615	Rollmark Caliber			
617	Drill and Tap Sight Holes			
618	Polish Barrel			
620	Apply Coatings (Barrel Action)			
	Apply Coating (Bolt)			
625	Final Assembly A) Clean inside of Bolt Assembly			
	B) Inspect Rear Firing Pin Hole for Chamfer in Bolt Head			
	C) Inspect Ejector Hole for Chamfer			
	D) Oil Firing Pin Ass'y			
	E) Adjust Trigger Pull to Min Setting and Stake			

OP. #	OP. NAME	READINGS	DATE	INITIAL
	BARBER - M24 0124250			
625 CONT.	F) SAFETY ON FORCE	<u>4</u> <u>4</u> <u>4</u>	<u>8-12-97</u>	<u>CK</u>
	G) SAFETY OFF FORCE	<u>2</u> <u>2</u> <u>2</u>	<u>8-12-97</u>	<u>CK</u>
	H) TRIGGER PULL TEST & RETAINABILITY			
	I) FIRING PIN INDENT	<u>.021</u> <u>.022</u> <u>.022</u>	<u>8-12-97</u>	<u>CK</u>
	J) ASSEMBLE STOCK		<u>8-8-97</u>	<u>CK</u>
	K) ASSEMBLE SWIVEL STUDS		<u>9-10-97</u>	<u>CK</u>
	L) ATTACH FRONT AND REAR SIGHT ASSEMBLIES		<u>8-8-97</u>	<u>CK</u>
	M) IRON SIGHT ALIGNMENT		<u>8-8-97</u>	<u>CK</u>
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERER CONTAINER		<u>8-8-97</u>	<u>CK</u>
640	GALLERY TEST AND TARGET	<u>WIND:</u>		
	A) MALFUNCTIONS	<u>L 150 R 50</u>	<u>9-4-97</u>	<u>AC</u>
	B) PIERCED PRIMERS		<u>9-4-97</u>	<u>AC</u>
645	INSPECT FOR LIVE AMMO		<u>9-4-97</u>	<u>AC</u>
655	FINAL INSPECTION			
	A) HEADSPACE		<u>9-10-97</u>	<u>CK</u>
	B) TRIGGER PULL	<u>2.49</u> <u>2.39</u> <u>2.49</u> <u>2.36</u> <u>2.39</u>	<u>9-6-97</u>	<u>CK</u>
	FUNCTION		<u>9-10-97</u>	<u>CK</u>
660	PACK			

Do Not Use

BARBER - M24 0124251

VERY IMPORTANT:
Instruction Book
enclosed to assure
safe use of this
firearm.

Remington®

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

Reg. U.S. Pat. & Tm. Off. Marca Registrada. Marque Déposée.

SERIAL NO.
E6349963

46

ORDER NO.
25705

15DR



5705 E6349963

ORDER 25705

MODEL 700™ M24

UPC



Do Not Use

ORDER 25705

MODEL 700™ M24

UPC



SERIAL NO.



E6349963

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

GREEN ENVELOPE CONTAINING:
- INSTRUCTION BOOK
- PRODUCT OWNER'S CARD
- MUSEUM/COUNTRY STORE FLIER
- REMINGTON AUTHORIZED GUNSMITHS

46 FORM

