

UPC



E6350074

ORDER NO. 25705
BARREL LENGTH 24"
CAPACITY * 6
*INCLUDES 1 IN CHAMBER

Do Not Use

VERY IMPORTANT
Instruction Book
enclosed to assure
safe use of this
weapon.

Remington®

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

Reg. U.S. Pat. & Tm. Off. Marca Registrada. Marque Deposee.

SERIAL NO.
E6350074

46 ORDER NO.
25705

04XR

5705 E6350074

ORDER 25705

MODEL 700™ M24

UPC



ORDER 25705

MODEL 700™ M24

UPC



SERIAL NO.



E6350074


Do Not Use

MODEL 700[™] M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

GREEN ENVELOPE CONTAINING:

- INSTRUCTION BOOK
- PRODUCT OWNER'S CARD
- MUSEUM/COUNTRY STORE FLIER
- REMINGTON AUTHORIZED GUNSMITHS

46 FORM



BARBER - M24 0125607

Remington Test Lab, Ilion, N.Y.

Centroidal distance calculations for Rifle # E6350074
9 Oct 1997

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: $-.145333$
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: $-.0633333$
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: $.158534$

THE AMR FOR THIS RIFLE IS: $.807$

CENTROIDAL DISTANCES

Ø TO	1	.232622
1 TO	2	.471068
1 TO	3	.176918

1
3+ <----POA
2

BARBER - M24 0125608

REMINGTON CENTERFIRE ACCURACY TEST


REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: ☐ 1 ☐

POA TO CENTROID: .232
MIN RADIUS : .306
MEAN RADIUS : .815
MAX RADIUS : 1.382
CENTROID X : -.188
CENTROID Y : .137

9 Oct 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/e6350074

CENTERFIRE PATTERN # 1

OF SHOTS= 5

IN CIRCLE

HS= 2.45

1

VS= .50

3

GS= 2.50


5

PATTERN #: 2
 POA TO CENTROID: .379
 MIN RADIUS : .037
 MEAN RADIUS : .821
 MAX RADIUS : 1.301
 CENTROID X : -.180
 CENTROID Y : -.334

9 Oct 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/e6350074

CENTERFIRE PATTERN # 2



OF SHOTS= 5

IN CIRCLE

HS= 1.85

1

VS= 1.74

3

GS= 2.08

5

BARBER - M24 0125610

REMINGTON CENTERFIRE ACCURACY TEST

REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: ☐ 3 ☐

POA TO CENTROID: .069

MIN RADIUS : .535

MEAN RADIUS : .785


MAX RADIUS : 1.122

CENTROID X : -.068

CENTROID Y : .007

9 Oct 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/e6350074

CENTERFIRE PATTERN # 3

OF SHOTS= 5

IN CIRCLE

HS= 2.08

0

VS= 1.14

3

GS= 2.12

5

ISRAELI GUNS

CONTRACT # DAAE20-97-C-0182

GUN SERIAL # E6350074

OP. #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK			
600	PROOF			
607	CHECK HEADSPACE			
610	DIS-ASSEMBLE GUN			
612	MAGNAFLUX BARREL ACTION			
	MAGNAFLUX BOLT			
615	ROLLMARK CALIBER			
617	DRILL AND TAP SIGHT HOLES			
618	POLISH BARREL			
620	APPLY COATINGS (BARREL ACTION)			
	(BOLT)			
625	FINAL ASSEMBLY A) CLEAN INSIDE OF BOLT ASSEMBLY			
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD			
	C) INSPECT EJECTOR HOLE FOR CHAMFER			
	D) OIL FIRING PIN ASSEMBLY			
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE			

OP. #	OPERATOR NAME	READINGS	DATE	INITIAL
625	F) SAFETY ON FORCE	<u>6</u> <u>4</u> <u>5</u>	10-3-97	CR
CONT.	G) SAFETY OFF FORCE	<u>3</u> <u>3</u> <u>3</u>	10-3-97	CR
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT	<u>.022</u> <u>.021</u> <u>.021</u>	10-3-97	CR
	J) ASSEMBLE STOCK		10/1/97	RW
	K) ASSEMBLE SWIVEL STUDS		10/15/97	
	L) ATTACH FRONT AND REAR SIGHT ASSY'S		10-1-97	RW
	M) IRON SIGHT ALIGNMENT		10-1-97	RW
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER		10-1-97	RW
640	GALLERY TEST AND TARGET	L67 R83	10-9-97	P.B.
	A) MALFUNCTIONS		10-9-97	P.B.
	B) PIERCED PRIMERS		10-9-97	P.B.
645	INSPECT FOR LIVE AMMO		10-9-97	LT
655	FINAL INSPECTION A) HEADSPACE		10/15/97	
	B) TRIGGER PULL	<u>2.57</u> <u>2.58</u> <u>2.49</u> <u>2.62</u> <u>2.63</u>	10-13-97	CR
	C) FUNCTION		10/15/97	RP

BARBER - M24 0125613

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# ± .50#

3.00# ± .75#

4.00# ± 1.00#

SERIAL NO. E6350074DATE 10-1-97TESTER TM

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#	COMMENTS
PULL #1	2.41	2.41	2.56	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.36	2.51	2.60	
PULL #3	2.37	2.50	2.64	
PULL #4	2.38	2.54	2.51	
PULL #5	2.30	2.56	2.60	
TOTAL	11.82	12.52	12.91	
AVG.	2.36	2.50	2.58	

	3.00# INITIAL	3.00# AFTER 20 CYCLES	COMMENTS
PULL #1	3.19	3.02	
PULL #2	3.18	3.03	
PULL #3	3.10	2.99	
PULL #4	3.06	3.04	
PULL #5	2.93	2.99	
TOTAL	15.46	15.07	
AVG.	3.09	3.01	

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.12	4.10		4.05
PULL #2	4.09	4.09		3.92
PULL #3	4.06	4.09		3.90
PULL #4	4.05	4.18		3.98
PULL #5	4.06	4.12		3.95
TOTAL	20.38	20.58		19.80
AVG.	4.07	4.11		3.96