GUN # A-3
REM MODEL 710
SERIAL # 71203229
30.06 CAL.

M/710 EXTRUDED RECEIVER TRIAL AND PILOT # 1

TLW 1689
PROJECT # 241314

NAME	DATE	TEST ACTIVITY	COMMENTS		RDS. FIRED	TOTAL RDS.
B. LEE	1-25-05	Initial Headspace	min .002	TLW1689B		
B. LEE	1-25-05	PRoof	OK	TLW1689C	1	1
B. LEE	1-25-05	Headspace	min .002	TLW1689D		
B. LEE	1-26-05	Firing Pin Indent	.022 .022-.022 Avg .022	TLW1689E		
B. LEE	1-28-05	Safe on/of Force	See data sheet	TLW1689I		
HJC	2-1-05	Weight/Screw depth	" "	TLW1689H		
B. LEE	2-2-05	Sear Eng/Lift	"	TLW1689F		
B. LEE	2-3-05	Trigger Pull	" "	TLW1689H		
B. LEE	2-4-05	Firing Pin Head Engagement	" "	TLW1689G		
HJC	2-7-05	Screw De-torque Forces	" "	TLW1689A		
B. LEE	2-8-05	Torque Screws to Specifications	Front 50 in lb - middle 30-35 in lb			
			Rear 18 in lb	TLW1689		
B. LEE	2-9-05	200 ed Jack Function		TLW1689L	200	201
B. LEE	2-16-05	extend function Endurance		TLW1689O	500	701
B. LEE	2-17-05	Clean/Inspection	see data Sheet	TLW1689R		
SW/JS	2/23/05	Safety Operation	5 mm PASS	TLW1689J		
"	"			"		
SW/JS	2/23/05	40 lb Trigger Pull Test (Remington Test)		TLW1689K		
"	"	Pass Before	Pin .437 After .437	"		
B. LEE	2-25-05	Shoulder function		TLW1689M	10	711
	2-25-05					

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

FORM DTDS.XLS

BARBER - 5.22.06r0005208

Confidential - Subject to Protective Order
Williams v. Remington

ET22208