

UPC



E6351247

ORDER NO. 25705

BARREL LENGTH 24"

CAPACITY * 6

*INCLUDES 1 IN CHAMBER

BARBER - M24 0126596

Remington Test Lab, Ilion, N.Y.

Centroidal distance calculations for Rifle # E6351247
9 Sep 1997

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: .0123333
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: -.158
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: .158481

THE AMR FOR THIS RIFLE IS: 1.291

CENTROIDAL DISTANCES

Ø TO	1	.442875
1 TO	2	.66851
1 TO	3	.268888

2 + <----POA
3
1

BARBER - M24 0126597

REMINGTON CENTERFIRE ACCURACY TEST


REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: 2
 POA TO CENTROID: .266
 MIN RADIUS : .206
 MEAN RADIUS : .682
 MAX RADIUS : 1.043
 CENTROID X : .192
 CENTROID Y : -.183

9 Sep 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6351247

CENTERFIRE PATTERN # 2



OF SHOTS= 5

IN CIRCLE

HS= .64
 VS= 1.87
 GS= 1.92

2
 4
 5

BARBER - M24 0126598

REMINGTON CENTERFIRE ACCURACY TEST


REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: 1
 POA TO CENTROID: .443
 MIN RADIUS : 1.148
 MEAN RADIUS : 1.794
 MAX RADIUS : 2.922
 CENTROID X : .093
 CENTROID Y : -.433

9 Sep 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6351247.1

CENTERFIRE PATTERN # 1



OF SHOTS= 5

IN CIRCLE

HS= 2.64

0

VS= 4.63

0

GS= 4.89

2

BARBER - M24 0126599


REMINGTON CENTERFIRE ACCURACY TEST

REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: 3
POA TO CENTROID: .286
MIN RADIUS : .746
MEAN RADIUS : 1.397
MAX RADIUS : 2.209
CENTROID X : -.248
CENTROID Y : .142

9 Sep 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6351247

CENTERFIRE PATTERN # 3

OF SHOTS= 5

IN CIRCLE

HS= 2.57

0

VS= 2.81

1

GS= 3.73

3

BARBER - M24 0126600

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50# ± .50#

3.00# ± .75#

4.00# ± 1.00#

SERIAL NO. E6351247DATE 8-14-97TESTER JM

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#	COMMENTS
PULL #1	2.47	2.40	2.64	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.40	2.49	2.60	
PULL #3	2.46	2.51	2.64	
PULL #4	2.42	2.47	2.77	
PULL #5	2.42	2.42	2.68	
TOTAL	12.17	12.29	13.33	
AVG.	2.434	2.458	2.666	

	3.00# INITIAL	3.00# AFTER 20 CYCLES	COMMENTS
PULL #1	3.10	3.18	
PULL #2	3.11	3.26	
PULL #3	3.21	3.18	
PULL #4	3.12	3.30	
PULL #5	3.21	3.27	
TOTAL	15.75	16.19	
AVG.	3.150	3.238	

	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	3.94	4.05		4.10
PULL #2	4.07	4.08		3.95
PULL #3	4.15	4.15		4.20
PULL #4	4.13	4.05		4.09
PULL #5	4.19	4.03		4.14
TOTAL	20.48	20.36		20.48
AVG.	4.096	4.072		4.096

ISRAELI GUNS

CONTRACT # DAAE20-97-C-0182

GUN SERIAL # E 6351247

OP. #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK			
600	PROOF			
607	CHECK HEADSPACE			
610	DIS-ASSEMBLE GUN			
612	MAGNAFLUX BARREL ACTION			
	MAGNAFLUX BOLT			
615	ROLLMARK CALIBER			
617	DRILL AND TAP SIGHT HOLES			
618	POLISH BARREL			
620	APPLY COATINGS (BARREL ACTION)			
	(BOLT)			
625	FINAL ASSEMBLY A) CLEAN INSIDE OF BOLT ASSEMBLY			
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD			
	C) INSPECT EJECTOR HOLE FOR CHAMFER			
	D) OIL FIRING PIN ASSEMBLY			
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE			


OP. #	OPERATION NAME	READINGS	DATE	INITIAL
625	F) SAFETY ON FORCE	<u>4</u> <u>4</u> <u>4</u>	9-8-97	CK
CONT.	G) SAFETY OFF FORCE	<u>2</u> <u>2</u> <u>2</u>	9-8-97	CK
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT	<u>.021</u> <u>.021</u> <u>.021</u>	9-8-97	CK
	J) ASSEMBLE STOCK		8-22-97	CR
	K) ASSEMBLE SWIVEL STUDS			
	L) ATTACH FRONT AND REAR SIGHT ASSY'S		8-22-97	CR
	M) IRON SIGHT ALIGNMENT		8-22-97	CR
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER		8-22-97	CR
640	GALLERY TEST AND TARGET	R 85 - L 62	9-9-97	KT
	A) MALFUNCTIONS		9-9-97	KT
	B) PIERCED PRIMERS		9-9-97	KT
645	INSPECT FOR LIVE AMMO		9-9-97	Ref
655	FINAL INSPECTION A) HEADSPACE		9-16-97	KL
	B) TRIGGER PULL	<u>2.39</u> <u>2.30</u> <u>2.29</u> <u>2.24</u> <u>2.20</u>	9/16/97	TMT
	C) FUNCTION			

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

GREEN ENVELOPE CONTAINING:

- INSTRUCTION BOOK
- PRODUCT OWNER'S CARD
- MUSEUM/COUNTRY STORE FLIER
- REMINGTON AUTHORIZED GUNSMITHS

46 FORM



Do Not Use

VERY IMPORTANT
Instruction Book
enclosed to assure
safe use of this
weapon.

Remington®

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

Reg. U.S. Pat. & Tr. Off. Marca Registrada. Marque Deposee.

SERIAL NO.
E6351247

48 ORDER NO.
25705

23DR

5705 E6351247

ORDER 25705

MODEL 700™ M24

UPC



ORDER 25705

MODEL 700™ M24

UPC



SERIAL NO.



E6351247