GUN # A-4
REM MODEL 710
SERIAL # 71202780
30.06 CAL.

M/710 EXTRUDED RECEIVER TRIAL AND PILOT # 1

TLW 1689
PROJECT # 241314

NAME	DATE	TEST ACTIVITY	COMMENTS		RDS. FIRED	TOTAL RDS.
B. LEE	1-25-05	Indial Headspace	min .003	TLW 1689 B		
B. LEE	1-25-05	PROOF	OK	TLW1689 C	1	1
B. LEE	1-25-05	Headspace	min	TLW1689 D		
B. LEE	1-26-05	Firing Pin Indent	.022 - .023 - .021	TLW1689 E		
B. LEE	1-28-05	Safe on / off Force	See data sheet	TLW1689 I		
HJC	2-1-05	Weight / screw depth	" " "	TLW1689 A		
B. LEE	2-2-05	Sear Eng / lift	" " "	TLW1689 F		
B. LEE	2-3-05	Trigger Pull	" " "	TLW1689 H		
B. LEE	2-4-05	Firing Pin Head Exposure	" " "	TLW1689 G		
HJC	2-7-05	Screw De-torque Forces	" " "	TLW1689 A		
B. LEE	2-8-05	Torque Screws to Specification	Front 50 in Lb - middle 30-35 in Lb -			
			Rear 15 in Lb	TLW 1689		
B. LEE	2-9-05	200 Rd Jack Function		TLW1689 L	200	201
B. LEE	2-16-05	Bend Function Endurance		TLW1689 O	500	211
B. LEE	2-17-05	Clean / Inspection	See DATA sheet	TLW1689 R		
B. LEE	2-24-05	Shoulder Function		TLW1689 M	40	211

THIS SHEET IS TO ACCOMPANY THE FIREARM AT ALL TIMES THROUGHOUT TESTING

83

FORM DTDS.XLS

BARBER - 5.22.06r0005219

Confidential - Subject to Protective Order
Williams v. Remington

ET22219