


UPC



E6374517

ORDER NO. 25705
BARREL LENGTH 24"
CAPACITY * 6
*INCLUDES 1 IN CHAMBER

Remington Test Lab, Ilion, N.Y.

Centroidal distance calculations for Rifle # E6374517
2 Dec 1997

THE AVERAGE X-COORDINATE FOR THIS RIFLE IS: $-.146667$
THE AVERAGE Y-COORDINATE FOR THIS RIFLE IS: $-.0803333$
THE RESULTING AVERAGE POI RADIUS FOR THIS RIFLE IS: $.167226$

THE AMR FOR THIS RIFLE IS: 1.014

CENTROIDAL DISTANCES

0 TO 1 .218257
1 TO 2 .197185
1 TO 3 .29642

3
2 1 + <----POA

REMINGTON CENTERFIRE ACCURACY TEST

REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: 116

POA TO CENTROID: .219

MIN RADIUS : .727

MEAN RADIUS : 1.294

MAX RADIUS : 1.810


CENTROID X : -.100

CENTROID Y : -.194

2 Dec 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6374517

CENTERFIRE PATTERN # 1



OF SHOTS= 5

IN CIRCLE

HS= 1.58

0

VS= 2.90

2

GS= 3.30


3

PATTERN #: 2
 POA TO CENTROID: .325
 MIN RADIUS : .359
 MEAN RADIUS : .892
 MAX RADIUS : 1.502
 CENTROID X : -.291
 CENTROID Y : -.145

2 Dec 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6374517

CENTERFIRE PATTERN # 2



OF SHOTS= 5

IN CIRCLE

HS= 1.63

1

VS= 2.39

2

GS= 2.56

4

BARBER - M24 0128050

° REMINGTON CENTERFIRE ACCURACY TEST


REMINGTON TEST LAB, ILION, N.Y.

PATTERN #: 3
 POA TO CENTROID: .110
 MIN RADIUS : .438
 MEAN RADIUS : .856
 MAX RADIUS : 1.386
 CENTROID X : -.049
 CENTROID Y : .098

2 Dec 1997

FILE:/Hpbasic/Accuracy/Patterning/Centerfire_Patt/E6374517

CENTERFIRE PATTERN # 3



OF SHOTS= 5

IN CIRCLE

HS= 2.20

1

VS= 1.22

4

GS= 2.27

5

ISRAELI GUNS

CONTRACT # DAAE20-97-C-0182

GUN SERIAL # E6374517

OP. #	OPERATION NAME	READINGS	DATE	INITIAL
575 & 580	ASSEMBLE ACTION AND STOCK			
600	PROOF			
607	CHECK HEADSPACE			
610	DIS-ASSEMBLE GUN			
612	MAGNAFLUX BARREL ACTION			
	MAGNAFLUX BOLT			
615	ROLLMARK CALIBER			
617	DRILL AND TAP SIGHT HOLES			
618	POLISH BARREL			
620	APPLY COATINGS (BARREL ACTION)			
	(BOLT)			
625	FINAL ASSEMBLY A) CLEAN INSIDE OF BOLT ASSEMBLY			
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD			
	C) INSPECT EJECTOR HOLE FOR CHAMFER			
	D) OIL FIRING PIN ASSEMBLY			
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE			

OP. #	OPERATION NAME	READINGS	DATE	INITIAL
625	BARBER M24-0128052 F) SAFETY ON FORCE	<u>5</u> <u>5</u> <u>5</u>	11-13-97	CR
CONT.	G) SAFETY OFF FORCE	<u>3</u> <u>3</u> <u>4</u>	11-13-97	CR
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT	<u>.023</u> <u>.023</u> <u>.023</u>	11-13-97	CR
	J) ASSEMBLE STOCK		11-12-97	CR
	K) ASSEMBLE SWIVEL STUDS			
	L) ATTACH FRONT AND REAR SIGHT ASSY'S		11-12-97	CR
	M) IRON SIGHT ALIGNMENT		11-12-97	CR
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER		11-12-97	CR
640	GALLERY TEST AND TARGET	L 60 R 90	12-2-97	DB
	A) MALFUNCTIONS		12-2-97	DB
	B) PIERCED PRIMERS		12-2-97	DB
645	INSPECT FOR LIVE AMMO		12-2-97	DB DE
655	FINAL INSPECTION A) HEADSPACE		12/9/97	RW
	B) TRIGGER PULL	<u>2.44</u> <u>2.45</u> <u>2.36</u> <u>2.49</u> <u>2.41</u>	12/4/97	TM
	C) FUNCTION			
660	PACK			

BARBER - M24 0128053

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50#+ .50#

3.00#+ .75#

4.00#+1.00#

SERIAL NO. EG374517DATE 11-12-97TESTER C/K

	2.50# INITIAL	2.50# AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50#		COMMENTS
PULL #1	2.63	2.69		2.38	MIN. SETTING, NO AVG. OF 5 READINGS ACCEPT- ABLE LESS THAN 2#
PULL #2	2.69	2.63		2.63	
PULL #3	2.60	2.70		2.69	
PULL #4	2.71	2.44		2.75	
PULL #5	2.61	2.34		2.61	
TOTAL	13.24	12.8		13.06	
AVG.	2.648	2.56		2.612	

	3.00# INITIAL	3.00# AFTER 20 CYCLES		COMMENTS
PULL #1	3.36	2.88		
PULL #2	3.13	3.03		
PULL #3	3.23	2.96		
PULL #4	3.17	3.13		
PULL #5	3.09	3.03		
TOTAL	15.98	15.03		
AVG.	3.196	3.006		


	4.00# INITIAL	4.00# AFTER 20 CYCLES	MAX SETTING GREATER THAN 4#	RESET TO 4# FOR TARGET & ACCURACY
PULL #1	4.00	4.04		4.02
PULL #2	4.15	3.73		4.10
PULL #3	3.94	3.91		3.93
PULL #4	4.07	3.72		4.05
PULL #5	4.16	3.91		4.07
TOTAL	20.32	19.31		20.17
AVG.	4.064	3.862		4.034

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

GREEN ENVELOPE CONTAINING:

- INSTRUCTION BOOK
- PRODUCT OWNER'S CARD
- MUSEUM/COUNTRY STORE FLIER
- REMINGTON AUTHORIZED GUNSMITHS

46 FORM



BARBER - M24 0128055

Do Not Use

Do Not Use

Lot #23

SERIAL NO.



E6374517

ORDER 25705

MODEL 700™ M24

UPC



0 47700 11 25705 1

ORDER 25705

MODEL 700™ M24

UPC



0 47700 11 25705 1

Remington®

MODEL 700™ M24
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO 6*

VERY IMPORTANT!
Instruction Book
enclosed to assure
safe use of this
rifle.

SERIAL NO.
E6374517

46 ORDER NO.
25705

11XR

5705 E6374517

Reg. U.S. Pat. & Tm. Off. Marca Registrada. Marque Déposée.

CONFIDENTIAL-SUBJECT TO PROTECTIVE ORDER
KINZER V. REMINGTON

BARBER - M24 0128055 28094