


G6761669

**MODEL 700<sup>TH</sup> EXPORT**  
**BOLT ACTION CENTERFIRE RIFLE**  
**24" BARREL 308 WIN**

ASK FOR THE PACKING CARTON  
INSTRUCTION BOOK 1918

120130 TURNER BLACK SLING  
96117 BI POD ASSY  
400054 COMPONENT CARRYING CASE  
1333 ETHAFOAM BLOCK (2)  
401937 SCOPE

**BM FORM 1799**




**ORDER NO. 86453**

**BARREL LENGTH 24"**

**CAPACITY 5**

**G6761669**



INSPECTION CHECKLIST  
COLUMBIAN EXPORT 5/2008

| OPERATION #   | OPERATION NAME               | DATE                                      | INITIAL     |
|---------------|------------------------------|-------------------------------------------|-------------|
| SERIAL NUMBER | G6761669                     |                                           |             |
| 440           | PROOF                        | 6-9-08                                    | TRW         |
| 460           | CHECK HEADSPACE              | 6-9-08                                    | TRW         |
| 470           | DIS-ASSEMBLE GUN             | 6-9-08                                    | RP          |
| 480           | MAGNAFLUX                    |                                           |             |
| 510           | DRILL AND TAP                | 6-9-08                                    | TRW         |
| 500           | ROLLMARK CALIBER $\neq$ WASH | 6-9-08                                    | CW          |
| 520           | GOFF BLAST BBL / REC         | 6-11-08                                   | IG          |
| 530 & 540     | APPLY COATINGS               | 6/6/08                                    | AF          |
| 560           | FINAL ASSEMBLY               | 8-19-08                                   | PSW         |
| 640           | FUNCTION TEST AND            | (PASS) FAIL                               | 8-20-08 TRW |
| 650           | TARGET                       | (PASS) FAIL                               | 8-20-08 TRW |
|               | MALFUNCTION                  | CORRECTION                                |             |
|               | MALFUNCTION                  | CORRECTION                                |             |
|               | MALFUNCTION                  | CORRECTION                                |             |
|               | MALFUNCTION                  | CORRECTION                                |             |
| 670           | FINAL INSPECTION             |                                           |             |
|               | A) HEADSPACE                 | (PASS) FAIL                               | 8/20/08 TRW |
|               | B) TRIGGER PULL              |                                           |             |
|               |                              | +/- .5 LBS<br>MIN 2.50 LBS<br>MAX 4.0 LBS |             |
| 680           | F) SAFETY ON FORCE           |                                           |             |
|               |                              | 2 LBS MIN<br>10 LBS MAX                   |             |
|               | G) SAFETY OFF FORCE          |                                           |             |
|               |                              | 2 LBS<br>MIN                              |             |
|               | I) FIRING PIN INDENT         |                                           |             |
|               |                              | .020                                      |             |
| 690           | PACK                         |                                           | 8/20/08 Fm  |

F006 REV 5/2006