



66761679

**MODEL 700<sup>TH</sup> EXPORT**  
**BOLT ACTION CENTERFIRE RIFLE**  
**24" BARREL 308 WIN**

ASK FOR THE PACKING CARTON  
INSTRUCTION BOOK 1918

120130 TURNER BLACK SLING  
96117 BI POD ASSY  
400054 COMPONENT CARRYING CASE  
1333 ETHAFOAM BLOCK (2)  
401937 SCOPE

BM FORM 1799




ORDER NO. **86453**

BARREL LENGTH 24"

CAPACITY 5

**G6761679**



INSPECTION CHECKLIST  
COLUMBIAN EXPORT 5/2008

| OPERATION #   | OPERATION NAME          | DATE                                      | INITIAL     |
|---------------|-------------------------|-------------------------------------------|-------------|
| SERIAL NUMBER | 56761679                |                                           |             |
| 440           | PROOF                   |                                           |             |
| 460           | CHECK HEADSPACE         |                                           |             |
| 470           | DIS-ASSEMBLE GUN        |                                           |             |
| 480           | MAGNATEUX               |                                           |             |
| 510           | DRILL AND TAP           | 7-29-08                                   | SP          |
| 500           | ROLLMARK CALIBER * NASH | 7/31/08                                   | RT          |
| 520           | GOFF BLAST BBL / REC    | 7/31                                      | DG          |
| 530 & 540     | APPLY COATINGS          | 8-6                                       |             |
| 560           | FINAL ASSEMBLY          | 8-12-08                                   | PSW         |
| 640           | FUNCTION TEST AND       | (PASS) FAIL                               | 8-14-08 TRW |
| 650           | TARGET                  | (PASS) FAIL                               | 8-14-08 TRW |
|               | MALFUNCTION             | CORRECTION                                |             |
|               | MALFUNCTION             | CORRECTION                                |             |
|               | MALFUNCTION             | CORRECTION                                |             |
|               | MALFUNCTION             | CORRECTION                                |             |
| 670           | FINAL INSPECTION        |                                           | 8-14-08 TC  |
|               | A) HEADSPACE            | (PASS) FAIL                               | 8-19-08 RTZ |
|               | B) TRIGGER PULL         | +/- .5 LBS<br>MIN 2.50 LBS<br>MAX 4.0 LBS |             |
| 680           | F) SAFETY ON FORCE      | 2 LBS MIN<br>10 LBS MAX                   |             |
|               | G) SAFETY OFF FORCE     | 2 LBS<br>MIN                              |             |
|               | I) FIRING PIN INDENT    | .020                                      |             |
| 690           | PACK                    |                                           | 8/19/08 PM  |

F006 REV 5/2006