


66764907

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase



owner registration sticker



BM FORM


ORDER NO. **86470**

BARREL LENGTH 24"

CAPACITY 6

G6764907

UPC



INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL #

G 6764907

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		7-15-08	PSN
430	ASSEMBLE TO STOCK		7-15-08	SP
440	PROOF		7-15-08	SP
460	CHECK HEADSPACE		7-15-08	SP
470	DIS-ASSEMBLE ACTION		7-16-08	RT
472	SERIALIZE BOLT HANDLE		7-16-08	RT
475	DRILL AND TAP SIGHT HOLES		7-19-08	SP
480	MAGNAFLUX BBL ACTION		7/25/08	BT
490	MAGNAFLUX BOLT			
500	ROLLMARK CALIBER		7/25/08	RT
520	GOFF BLAST BBL / REC		7/25/08	DS
542	APPLY COATINGS (BARREL ACTION)		8-2	
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		8-4-08	PSN
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		8-4-08	PSN
	C) INSPECT EJECTOR HOLE FOR CHAMFER		8-4-08	PSN
	D) OIL FIRING PIN ASSEMBLY		8-6-08	PSN
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS		

F004 REV 5/2006

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>2.5</u> <u>7</u> <u>7</u>	8-21	TL
CONT.				
	G) SAFETY OFF FORCE 2 LBS MIN	<u>7</u> <u>7</u> <u>7</u>	8-21	TL
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.024</u> <u>.023</u> <u>.024</u>	8-21	TL
	J) ASSEMBLE STOCK		8-6-08	PSN
	K) ASSEMBLE SWIVEL STUDS		8-26	TL
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	8-7-08	TRW
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		8-7-08	TL
670	FINAL INSPECTION A) HEADSPACE		8-26	TL
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.72</u> <u>2.62</u> <u>2.58</u> <u>2.61</u> <u>2.65</u>	8/15/08	Fm
	C) FUNCTION		8-26	TL
690	PACK		8-27-08	TL

F004 REV 5/2006

BARBER - M24 0128660AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)

3.00 LBS (plus or minus 0.75 LBS)

4.00 LBS (plus or minus 1.00 LBS)

DATE

8-1-08

TESTER

RP

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	2.61	2.62		2.69	
PULL #2	2.54	2.54		2.69	
PULL #3	2.38	2.57		2.77	
PULL #4	2.50	2.58		2.80	
PULL #5	2.45	2.54		2.74	
TOTAL	12.48	12.85		13.69	
AVERAGE	2.49	2.57		2.73	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	3.18	3.24		
PULL #2	3.16	3.33		
PULL #3	3.16	3.35		
PULL #4	3.08	3.37		
PULL #5	3.16	3.37		
TOTAL	15.74	16.66		
AVERAGE	3.14	3.33		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	4.18	4.34		4.27
PULL #2	4.11	4.08		4.12
PULL #3	4.09	4.04		4.12
PULL #4	4.12	3.97		4.09
PULL #5	4.19	4.07		4.07
TOTAL	20.69	20.50		20.67
AVERAGE	4.13	4.10		4.13