

66764914

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase



owner registration sticker




BM FORM

ORDER NO.	86470
BARREL LENGTH	24"
CAPACITY	6

G6764914

UPC



INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL # G6764914

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		6-18-08	J.P.D.
430	ASSEMBLE TO STOCK		6-18-08	SP
440	PROOF		6-18-08	SD
460	CHECK HEADSPACE		6-18-08	SD
470	DIS-ASSEMBLE ACTION		6-18-08	J.P.D.
472	SERIALIZE BOLT HANDLE		6-20-08	J.P.D.
475	DRILL AND TAP SIGHT HOLES	MAGNA - FLUX JUN 20 2008 OPERATOR WMS	6-23-08	SP
480	MAGNAFLUX BBL ACTION		6-24-08	WMS
490	MAGNAFLUX BOLT			
500	ROLLMARK CALIBER		6-24-08	RT
520	GOFF BLAST BBL / REC		6-25	BL
542	APPLY COATINGS (BARREL ACTION)		7-13	CM
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		7-14-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		7-14-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		7-14-08	SP
	D) OIL FIRING PIN ASSEMBLY		7-15-08	J.P.D.
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS			

F004 REV 5/2006

CP #		BARBER - M24 0128735			READINGS			DATE	INITIAL
560	F) SAFETY ON FORCE	2 LBS MIN 10 LBS MAX	<u>8</u>	<u>8</u>	<u>8</u>	<u>7-22</u>	<u>TL</u>		
CONT.									
	G) SAFETY OFF FORCE	2 LBS MIN	<u>6</u>	<u>6</u>	<u>6</u>	<u>7-22</u>	<u>TL</u>		
	H) TRIGGER PULL TEST AND RETAINABILITY								
	I) FIRING PIN INDENT	.020 MIN	<u>.022</u>	<u>.023</u>	<u>.023</u>	<u>7-22</u>	<u>TL</u>		
	J) ASSEMBLE STOCK					<u>7-15-08</u>	<u>R.P.D</u>		
	K) ASSEMBLE SWIVEL STUDS					<u>7-30-08</u>	<u>RTZ</u>		
	L) ATTACH FRONT AND REAR SIGHT ASSY'S					<u>—</u>			
	M) IRON SIGHT ALIGNMENT					<u>—</u>			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER					<u>—</u>			
640 & 650	FUNCTION TEST AND TARGET		<u>PASS</u>		FAIL				
			<u>PASS</u>		FAIL	<u>7-16-08</u>	<u>TRW</u>		
	MALFUNCTION								
	MALFUNCTION								
	MALFUNCTION								
	MALFUNCTION								
660	INSPECT FOR LIVE AMMO					<u>7/14/08</u>	<u>MED</u>		
670	FINAL INSPECTION A) HEADSPACE					<u>7-30-08</u>	<u>RTZ</u>		
	B) TRIGGER PULL	+/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.53</u>	<u>2.47</u>	<u>2.47</u>	<u>2.42</u>	<u>2.42</u>	<u>7/22/08</u>	<u>Fm</u>
	C) FUNCTION					<u>7-30-08</u>	<u>RTZ</u>		
690	PACK					<u>7/31/08</u>	<u>Fm</u>		

F004 REV 5/2006

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)
 3.00 LBS (plus or minus 0.75 LBS)
 4.00 LBS (plus or minus 1.00 LBS)

DATE 7-10-08

TESTER TRW

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	2.38	2.32		2.26	
PULL #2	2.69	2.38		2.25	
PULL #3	2.70	2.39		2.31	
PULL #4	2.72	2.32		2.27	
PULL #5	2.32	2.32		2.33	
TOTAL	12.81	11.73		11.42	
AVERAGE	2.56	2.34			

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	3.16	3.19		
PULL #2	3.43	3.14		
PULL #3	3.37	3.15		
PULL #4	3.29	3.20		
PULL #5	3.40	3.27		
TOTAL	16.65	15.95		
AVERAGE	3.33	3.19		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	4.12	4.07		4.49
PULL #2	4.06	4.01		4.22
PULL #3	4.35	4.09		4.37
PULL #4	4.51	4.07		4.49
PULL #5	4.43	4.07		4.45
TOTAL	21.47	20.31		22.02
AVERAGE	4.29	4.06		4.40