

66764923

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)

BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase



owner registration sticker



BM FORM


ORDER NO. **86470**

BARREL LENGTH 24"

CAPACITY 6

G6764923

UPC



GUN SERIAL # G 6764923

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		6-24-08	RP
430	ASSEMBLE TO STOCK		6-24-08	SP
440	PROOF		6-24-08	SD
460	CHECK HEADSPACE		6-24-08	SD
470	DIS-ASSEMBLE ACTION		6-24-08	RP
472	SERIALIZE BOLT HANDLE		7-10-08	RP
475	DRILL AND TAP SIGHT HOLES		6-24-08	SD
480	MAGNAFLUX BBL ACTION		7-15-08	(HS)
490	MAGNAFLUX BOLT			
500	ROLLMARK CALIBER		7/11/08	RT
520	GOFF BLAST BBL / REC		7	
542	APPLY COATINGS (BARREL ACTION)		7-21	CR
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		7-22-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		7-22-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		7-22-08	SP
	D) OIL FIRING PIN ASSEMBLY		7-24-08	BSN
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS			

F004 REV 5/2006

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>6.5</u> <u>6</u> <u>6</u>	<u>8-5</u>	<u>TL</u>
CONT.				
	G) SAFETY OFF FORCE 2 LBS MIN	<u>7</u> <u>6.5</u> <u>6.5</u>	<u>8-5</u>	<u>TL</u>
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.025</u> <u>.025</u> <u>.024</u>	<u>8-5</u>	<u>TL</u>
	J) ASSEMBLE STOCK		<u>7-27-08</u>	<u>RSW</u>
	K) ASSEMBLE SWIVEL STUDS		<u>8-27-08</u>	<u>RSW</u>
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	<u>7-26-08</u>	<u>TRW</u>
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		<u>7-26-08</u>	<u>TL</u>
670	FINAL INSPECTION A) HEADSPACE		<u>8-27-08</u>	<u>RSW</u>
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.48</u> <u>2.48</u> <u>2.45</u> <u>2.42</u> <u>2.31</u>	<u>8-4-08</u>	<u>RSW</u>
	C) FUNCTION		<u>8-27-08</u>	<u>RSW</u>
690	PACK		<u>9-3-08</u>	<u>TL</u>

F004 REV 5/2006

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

2.50 LBS (plus or minus 0.50 LBS)
 3.00 LBS (plus or minus 0.75 LBS)
 4.00 LBS (plus or minus 1.00 LBS)

DATE

7-21-08

TESTER

S. Day

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	2.71	2.31		2.29	
PULL #2	2.71	2.58		2.29	
PULL #3	2.70	2.55		2.30	
PULL #4	2.69	2.50		2.29	
PULL #5	2.62	2.47		2.31	
TOTAL	1343	1241		1148	
AVERAGE	268	248		2.29	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	3.06	3.40		
PULL #2	3.05	3.44		
PULL #3	3.12	3.37		
PULL #4	3.13	3.33		
PULL #5	3.16	3.32		
TOTAL	1552	1686		
AVERAGE	3.10	3.37		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	4.27	4.53		4.04
PULL #2	4.03	4.28		4.17
PULL #3	4.17	4.15		4.10
PULL #4	4.08	4.04		4.08
PULL #5	4.06	4.03		4.09
TOTAL	2061	2103		2048
AVERAGE	4.12	4.20		4.09