



No. 2-153L-3
ID# 10337

66765002

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase



owner registration sticker



BM FORM


ORDER NO. **86470**

BARREL LENGTH 24"

CAPACITY 6

G6765002

UPC



GUN SERIAL # G 6765002

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		6-18-08	SPD
430	ASSEMBLE TO STOCK		6-18-08	SP
440	PROOF		6-18-08	SD
460	CHECK HEADSPACE		6-18-08	SD
470	DIS-ASSEMBLE ACTION		6-18-08	SPD
472	SERIALIZE BOLT HANDLE		6-20-08	SPD
475	DRILL AND TAP SIGHT HOLES	MAGNA-FLUX JUN 20 2008 OPERATOR WMS	6-23-08	SD
480	MAGNAFLUX BBL ACTION		6-24-08	WMS
490	MAGNAFLUX BOLT			
500	ROLLMARK CALIBER		6-24-08	RT
520	GOFF BLAST BBL / REC		6-24	RT
542	APPLY COATINGS (BARREL ACTION)		7-8	W
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		7-9	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		7-9	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		7-9	SP
	D) OIL FIRING PIN ASSEMBLY		7-15-08	BSW
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS		

F004 REV 5/2006


OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>7</u> <u>7</u> <u>7</u>	7-22	TC
CONT.				
	G) SAFETY OFF FORCE 2 LBS MIN	<u>6</u> <u>6</u> <u>6</u>	7-22	TC
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.021</u> <u>.022</u> <u>.022</u>	7-22	TC
	J) ASSEMBLE STOCK		7-15-08	PSN
	K) ASSEMBLE SWIVEL STUDS		7-30-08	RTZ
	L) ATTACH FRONT AND REAR SIGHT ASSY'S		—	
	M) IRON SIGHT ALIGNMENT		—	
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER		—	
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	7-16-08	TRW
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		7/16/08	MEK
670	FINAL INSPECTION A) HEADSPACE		7-30-08	RTZ
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.62</u> <u>2.66</u> <u>2.60</u> <u>2.58</u> <u>2.50</u>	7/22/08	FM
	C) FUNCTION		7-30-08	RTZ
690	PACK		7/31/08	FM

F004 REV 5/2006

Trigger Profile [lbs,inch]

Profile SWS
GunType: Rifle
Make: Remington
Note: R. Putch 7/14/08

Model: M/24
Serial No: Form #F005
Trigger: 2.5 lbs. ini. +/- .50 lbs.




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	2.711	0.053	0.033	0.034	0.052		Set Trigger
2	2.664	0.054	0.034	0.033	0.052		Set Trigger
3	2.685	0.053	0.034	0.033	0.052		Set Trigger
4	2.769	0.053	0.034	0.033	0.053		Set Trigger
5	2.663	0.054	0.034	0.033	0.052		Set Trigger

Avg 2.69

Trigger Profile [lbs,inch]

Profile SWS
 GunType: Rifle
 Make: Remington
 Note: R. Putch 7/14/08

Model: M/24
 Serial No: Form #F005
 Trigger: 2.5 lbs. after 50 cycles +/- .50 lbs.




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	2.534	0.051	0.031	0.033	0.049		Set Trigger
2	2.603	0.050	0.031	0.033	0.048		Set Trigger
3	2.653	0.051	0.032	0.033	0.048		Set Trigger
4	2.593	0.049	0.032	0.033	0.045		Set Trigger
5	2.481	0.049	0.031	0.033	0.045		Set Trigger

Avg 2.57

Trigger Profile [lbs,inch]

Profile SWS
 GunType: Rifle
 Make: Remington
 Note: R. Putch 7/14/08

Model: M/24
 Serial No: Form #F005
 Trigger: 3.0 lbs. ini. +/- .75 lbs.




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	3.135	0.053	0.033	0.032	0.059		Set Trigger
2	3.080	0.053	0.032	0.032	0.060		Set Trigger
3	3.129	0.052	0.032	0.033	0.059		Set Trigger
4	3.160	0.052	0.032	0.032	0.060		Set Trigger
5	3.244	0.052	0.033	0.032	0.060		Set Trigger

Avg 3.15

Trigger Profile [lbs,inch]

Profile SWS
GunType: Rifle
Make: Remington
Note: R. Putch 7/14/08

Model: M24
Serial No: Form #F005
Trigger: 3.0 lbs. after 20 cycles +/- .75 lbs.




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	3.080	0.055	0.035	0.033	0.057		Set Trigger
2	3.089	0.054	0.035	0.033	0.057		Set Trigger
3	3.088	0.054	0.035	0.033	0.056		Set Trigger
4	3.001	0.055	0.035	0.033	0.056		Set Trigger
5	3.111	0.054	0.035	0.033	0.057		Set Trigger

Avg 3.07

Trigger Profile [lbs,inch]

Profile SWS
 GunType: Rifle
 Make: Remington
 Note: R. Putch 7/14/08

Model: M/24
 Serial No: Form #F005
 Trigger: 4.0 lbs. ini. +/- 1.0 lbs.




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	4.020	0.055	0.032	0.031	0.080		Set Trigger
2	4.006	0.055	0.032	0.031	0.080		Set Trigger
3	4.053	0.054	0.032	0.031	0.079		Set Trigger
4	4.058	0.054	0.032	0.031	0.080		Set Trigger
5	4.128	0.055	0.032	0.031	0.082		Set Trigger

Avg 4.05

Trigger Profile [lbs,inch]

Profile SWS
GunType: Rifle
Make: Remington
Note: R. Putch 7/14/08

Model: M/24
Serial No: Form #F005
Trigger: 4.0 lbs. after 20 cycles +/- 1.0 lbs.




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	3.999	0.053	0.031	0.030	0.079		Set Trigger
2	4.005	0.053	0.031	0.030	0.079		Set Trigger
3	4.066	0.053	0.031	0.030	0.081		Set Trigger
4	3.992	0.054	0.031	0.030	0.080		Set Trigger
5	3.989	0.053	0.031	0.030	0.079		Set Trigger

AVG 4.01

Trigger Profile [lbs,inch]

Profile SWS
GunType: Rifle
Make: Remington
Note: R. Putch 7/14/08

Model: M/24
Serial No: Form #F005
Trigger: reset to 2.5 lbs. +/- .50 lbs. for final test




#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	2.726	0.052	0.033	0.033	0.051		Set Trigger
2	2.793	0.053	0.033	0.033	0.052		Set Trigger
3	2.684	0.052	0.033	0.034	0.050		Set Trigger
4	2.778	0.052	0.034	0.033	0.051		Set Trigger
5	2.803	0.052	0.034	0.034	0.051		Set Trigger

Avg 2.75

Trigger Profile [lbs,inch]

Profile SWS
GunType: Rifle
Make: Remington
Note: R. Putch 7/14/08

Model: M/24
Serial No: Form #F005
Trigger: set to 4.0 lbs. +/- 1.0 lbs. for target & accuracy



#	Peak Force	Travel To Actuate	Initial Take-up	Overtravel	Energy To Actuate	Lock Time	Action Type
1	4.128	0.056	0.033	0.030	0.083		Set Trigger
2	4.088	0.056	0.034	0.030	0.081		Set Trigger
3	4.116	0.056	0.034	0.030	0.082		Set Trigger
4	4.153	0.055	0.033	0.031	0.082		Set Trigger
5	4.096	0.056	0.033	0.030	0.083		Set Trigger

Avg 4.11