

66765008

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase



owner registration sticker



BM FORM


ORDER NO. 86470

BARREL LENGTH 24"

CAPACITY 6

G6765008

UPC



INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL # 6 676500 8

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		7-22-08	PSN
430	ASSEMBLE TO STOCK		7-23-08	TRW
440	PROOF		7-23-08	TRW
460	CHECK HEADSPACE		7-23-08	TRW
470	DIS-ASSEMBLE ACTION		7-24-08	RJZ
472	SERIALIZE BOLT HANDLE		7-24-08	RJZ
475	DRILL AND TAP SIGHT HOLES		7-24-08	SD
480	MAGNAFLUX BBL ACTION		7/25/08	BH
490	MAGNAFLUX BOLT			
500	ROLLMARK CALIBER		7/25/08	RT
520	GOFF BLAST BBL / REC		7/25/08	DC
542	APPLY COATINGS (BARREL ACTION)		7/31	
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		8-5-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		8-5-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		8-5-08	SP
	D) OIL FIRING PIN ASSEMBLY		8-8-08	PSN
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE	2.50 LBS +/- .5 LBS		

OP #	OPERATION NAME	READINGS	DATE	INITIAL
560	F) SAFETY ON FORCE 2 LBS MIN 10 LBS MAX	<u>5.5</u> <u>5.5</u> <u>5.5</u>	8-14	TL
CONT.				
	G) SAFETY OFF FORCE 2 LBS MIN	<u>6</u> <u>6</u> <u>6</u>	8-14	TL
	H) TRIGGER PULL TEST AND RETAINABILITY			
	I) FIRING PIN INDENT .020 MIN	<u>.024</u> <u>.024</u> <u>.023</u>	8-14	TL
	J) ASSEMBLE STOCK		8-8-08	BSN
	K) ASSEMBLE SWIVEL STUDS		8-26	TL
	L) ATTACH FRONT AND REAR SIGHT ASSY'S			
	M) IRON SIGHT ALIGNMENT			
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER			
640 & 650	FUNCTION TEST AND TARGET	<u>PASS</u> FAIL <u>PASS</u> FAIL	8-8-08	TRW
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
	MALFUNCTION	CORRECTION		
660	INSPECT FOR LIVE AMMO		8-8-08	TL
670	FINAL INSPECTION A) HEADSPACE		8-26	TL
	B) TRIGGER PULL +/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>2.52</u> <u>2.28</u> <u>2.47</u> <u>2.26</u> <u>2.38</u>	8/14/08	Fm
	C) FUNCTION		8-26	TL
690	PACK		8-27-08	TL

F004 REV 5/2006

BARBER - M24 0129739

 AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS

 2.50 LBS (plus or minus 0.50 LBS)
 3.00 LBS (plus or minus 0.75 LBS)
 4.00 LBS (plus or minus 1.00 LBS)

 DATE 7-30-08

 TESTER RP

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	2.61	2.56		2.51	
PULL #2	2.61	2.62		2.48	
PULL #3	2.36	2.52		2.50	
PULL #4	2.59	2.70		2.47	
PULL #5	2.61	2.60		2.43	
TOTAL	12.78	13.00		12.39	
AVERAGE	2.55	2.60		2.47	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	3.14	3.21		
PULL #2	3.27	3.44		
PULL #3	3.25	3.14		
PULL #4	3.21	3.13		
PULL #5	3.20	3.15		
TOTAL	16.07	16.07		
AVERAGE	3.21	3.21		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	4.20	4.33		4.21
PULL #2	4.29	4.28		4.24
PULL #3	4.26	4.24		4.21
PULL #4	4.02	4.21		4.18
PULL #5	4.37	4.22		4.26
TOTAL	21.14	21.28		21.10
AVERAGE	4.22	4.25		4.22