


G 676 5019

M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)
BOLT ACTION CENTERFIRE RIFLE
24" BARREL 7.62 NATO
WITH BIPOD

proof of purchase



owner registration sticker




BM FORM

ORDER NO. **86470**

BARREL LENGTH 24"

CAPACITY 6

G6765019**UPC**

INSPECTION CHECKLIST-NEW GUNS

GUN SERIAL # G 6765019

OP #	OPERATION NAME	READINGS	DATE	INITIAL
420	ASSEMBLE ACTION		7-15-08	RSW
430	ASSEMBLE TO STOCK		7-15-08	SP
440	PROOF		7-15-08	J.P.D.
460	CHECK HEADSPACE		7-15-08	J.P.D.
470	DIS-ASSEMBLE ACTION		7-16-08	RT
472	SERIALIZE BOLT HANDLE		7-16-08	RT
475	DRILL AND TAP SIGHT HOLES		7-17-08	SP
480	MAGNAFLUX BBL ACTION		7-21-08	BN
490	MAGNAFLUX BOLT			
500	ROLLMARK CALIBER		7/21/08	RT
520	GOFF BLAST BBL / REC			
542	APPLY COATINGS (BARREL ACTION)		7-25	u
545	(BOLT)			
560	RE-ASSEMBLE ACTION			
	A) CLEAN INSIDE OF BOLT ASSEMBLY		7-29-08	SP
	B) INSPECT REAR FIRING PIN HOLE FOR CHAMFER IN BOLT HEAD		7-29-08	SP
	C) INSPECT EJECTOR HOLE FOR CHAMFER		7-29-08	SP
	D) OIL FIRING PIN ASSEMBLY		7-31-08	BSN
	E) ADJUST TRIGGER PULL TO MIN. SETTING AND STAKE 2.50 LBS +/- .5 LBS			

F004 REV 5/2006

ITEM #	DESCRIPTION	REQUIREMENTS	READINGS			DATE	INITIALS		
560	F) SAFETY ON FORCE	2 LBS MIN 10 LBS MAX	<u>5</u>	<u>5</u>	<u>4.5</u>	8-4	TC		
CONT.									
	G) SAFETY OFF FORCE	2 LBS MIN	<u>3.5</u>	<u>3</u>	<u>3.5</u>	8-4	TC		
	H) TRIGGER PULL TEST AND RETAINABILITY								
	I) FIRING PIN INDENT	.020 MIN	<u>.023</u>	<u>.023</u>	<u>.023</u>	8-4	TC		
	J) ASSEMBLE STOCK					7-31-08	ESN		
	K) ASSEMBLE SWIVEL STUDS					8-5-08	S.P.D.		
	L) ATTACH FRONT AND REAR SIGHT ASSY'S					8-5-08	S.P.D.		
	M) IRON SIGHT ALIGNMENT					8-5-08	S.P.D.		
	N) DETACH FRONT AND REAR SIGHTS AND PLACE IN NUMBERED CONTAINER								
640 & 650	FUNCTION TEST AND TARGET		<u>PASS</u>	FAIL		8-1-08	TRW		
			<u>PASS</u>	FAIL					
	MALFUNCTION	CORRECTION	N/A						
	MALFUNCTION	CORRECTION							
	MALFUNCTION	CORRECTION							
	MALFUNCTION	CORRECTION							
660	INSPECT FOR LIVE AMMO					8-1-08	TC		
670	FINAL INSPECTION A) HEADSPACE					8-5-08	S.P.D.		
	B) TRIGGER PULL	+/- .5 LBS MIN 2.50 LBS MAX 4.0 LBS	<u>259</u>	<u>248</u>	<u>225</u>	<u>220</u>	<u>248</u>	8-4-08	ESN
	C) FUNCTION					8-5-08	S.P.D.		
690	PACK					8/7/08	Fm		

AVERAGE PULL FORCE BETWEEN
INITIAL & CYCLE TESTS:

2.50 LBS (plus or minus 0.50 LBS)
 3.00 LBS (plus or minus 0.75 LBS)
 4.00 LBS (plus or minus 1.00 LBS)

DATE 7-24-08

TESTER S. Day

	2.50 LBS INITIAL	2.50 LBS AFTER 50 CYCLES	FINAL TEST & TO RESET 2.50 LBS		COMMENTS
PULL #1	2.64	2.53		2.51	
PULL #2	2.63	2.36		2.66	
PULL #3	2.53	2.31		2.56	
PULL #4	2.47	2.35		2.54	
PULL #5	2.53	2.35		2.71	
TOTAL	1280	1190		1298	
AVERAGE	2.56	2.38		2.59	

	3.00 LBS INITIAL	3.00 LBS AFTER 20 CYCLES		COMMENTS
PULL #1	3.23	3.42		
PULL #2	3.21	3.32		
PULL #3	3.17	3.18		
PULL #4	3.29	3.16		
PULL #5	3.11	3.17		
TOTAL	1601	1625		
AVERAGE	3.20	3.25		

	4.00 LBS INITIAL	4.00 LBS AFTER 20 CYCLES	MAX SETTING GREATER THAN 4 LBS	RESET TO 4 LBS FOR TARGET & ACCURACY
PULL #1	4.09	4.23		4.27
PULL #2	4.10	4.21		4.09
PULL #3	4.17	4.15		4.00
PULL #4	4.05	4.12		4.09
PULL #5	4.10	4.10		4.03
TOTAL	2051	2081		2048
AVERAGE	4.10	4.16		4.09