

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-10

TLW #: TLW1216

Date: 8 / 20 / 03Inspector: SW/BLRound Level: 221☒ Measure Headspace min+.007☒ Sear Engagement: 1st. .0247 2nd. .0249 3rd. .0249 Ave. .02483 spec- .020" to .025" 83☐ Reset Sear Engagement if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____☒ Trigger Pull: 1st. 4.192 2nd. 4.187 3rd. 4.251 Ave. 4.210 spec- 4 lb. to 5.5 lb.☐ Reset Trigger Pull if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: _____☒ Inspect stock for any signs of cracking or otherfailure. Lower corners of recoil bracket has cracks on stock,
cracks on middle take down screw hole.☒ Other items ofnote: Top of magazine box has some protrusion, wear in
magazine latch area

TLW1216

Remington Confidential

ET22298