

TLW 1216AAProject No. 241314**EXTENDED ROTATION TEST**

Firecontrol No. A-10 Firecontrol Type: STANDARD Date: 9-19-03
 Dry Cycles/Rounds Completed: _____ Stock Type _____ Engagement at Start .0205
 Model No. _____ Serial No. _____ Engagement at End .02063
 Trigger Pull at Start of Test (1) 4.087 (2) 4.028 (3) 4.120 (4) 4.013 (5) 4.065 (6) —
 Average Trigger Pull at Start of Test: 4.063 Std. Dev. of Trigger Pull at Start of Test: _____
 Trigger Pull at End of Test (1) 3.662 (2) 3.807 (3) 3.791 (4) 3.882 (5) 3.905 (6) —
 Average Trigger Pull at End of Test: 3.809 Std. Dev. of Trigger Pull at End of Test: _____

Tester Initials: _____

Additional Notes and Comments

SAAMI Specifications for Standard Rotation Test do not apply to this test.

Extended Rotation Test: Rest Firearm on the Butt end and allow Firearm to fall
 Drop - onto Tile Floor backed by Concrete. NO RUBBER MATT
 Firearm not ready to fire, Safe in "Safe" position, Fresh Primed Case
 in Chamber, Magazine loaded to capacity with Dummy Rounds.
 After each drop, Fire Primed Case to verify firearm will still function.

"Rotation Test" (safety in "Safe" position) - one drop per orientation.

***Note: for Firearms with the ISS system installed - The Firearms will be set with the
 ISS system in the unlocked position for both orientations of the Rotation Test.***

Orientation	ISS Unlocked	Comments
Firearm Vertical, Drop so left side of Stock is Up:	Pass <input checked="" type="checkbox"/> Fail _____	_____
Firearm Vertical, Drop so right side of Stock is Up:	Pass <input checked="" type="checkbox"/> Fail _____	_____

Notes: (continue on back of sheet if necessary)

Tester's Initials _____

ET22312