

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-9

TLW #: TLW1216

Date: 9 / 8 / 03

Inspector: SW/RL

Round Level: 741

☒ Measure Headspace Mint .007

☒ Sear Engagement: 1st. .0260 2nd. .0259 3rd. .0259

Ave. .02595 spec- .020" to .025"

☒ Reset Sear Engagement if Required: 1st. .0223 2nd. .0224 3rd. .0226

Ave. .02243

☒ Trigger Pull: 1st. 4.478 2nd. 4.512 3rd. 4.462

Ave. 4.484 spec- 4 lb. to 5.5 lb.

☒ Reset Trigger Pull if Required: 1st. 4.309 2nd. 4.442 3rd. 4.334

Ave. 4.361

☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: Normal wear, wear on bolt latch

☒ Inspect stock for any signs of cracking or other failure. CRACKS in stock

☒ Other items of

note: Top of magazine box has some protrusion, wear in
magazine latch area Photo taken

TLW1216

Remington Confidential

ET22342