

6674 9173

**M/24 7.62 NATO S.W.S. (COMPLETE SYSTEM)**  
**BOLT ACTION CENTERFIRE RIFLE**  
**24" BARREL 7.62 NATO**  
**WITH BIPOD**

proof of purchase



owner registration sticker




ORDER NO. **86470**

BARREL LENGTH **24"**

CAPACITY **6**

**G6749173**

**UPC**



BM FORM

GUN SERIAL # G 6749173

| OP # | OPERATION NAME                                                                                                                         | READINGS            | DATE    | INITIAL    |
|------|----------------------------------------------------------------------------------------------------------------------------------------|---------------------|---------|------------|
| 420  | ASSEMBLE ACTION                                                                                                                        |                     | 6-12-08 | RP         |
| 430  | ASSEMBLE TO STOCK                                                                                                                      |                     | 6-13-08 | SP         |
| 440  | PROOF                                                                                                                                  |                     | 6-13-08 | SD         |
| 460  | CHECK HEADSPACE                                                                                                                        |                     | 6-13-08 | SD         |
| 470  | DIS-ASSEMBLE ACTION                                                                                                                    |                     | 6-13-08 | RP         |
| 472  | SERIALIZE BOLT HANDLE                                                                                                                  | MAGNA - FLUX        | 6-18-08 | L.P.D.     |
| 475  | DRILL AND TAP<br>SIGHT HOLES                                                                                                           | JUN 1 2008          | 6-17-08 | SP         |
| 480  | MAGNAFLUX BBL ACTION                                                                                                                   | OPERATOR <i>WMS</i> | 6/18/08 | <i>WMS</i> |
| 490  | MAGNAFLUX BOLT                                                                                                                         |                     |         |            |
| 500  | ROLLMARK CALIBER                                                                                                                       |                     | 6/18/08 | RT         |
| 520  | GOFF BLAST BBL / REC                                                                                                                   |                     | 6/18/08 | BT         |
| 542  | APPLY COATINGS<br>(BARREL ACTION)                                                                                                      |                     | 6/18/08 | <i>W</i>   |
| 545  | (BOLT)                                                                                                                                 |                     |         |            |
| 560  | RE-ASSEMBLE ACTION                                                                                                                     |                     | 6/19/08 | RP         |
|      | A) CLEAN INSIDE OF<br>BOLT ASSEMBLY                                                                                                    |                     |         |            |
|      | B) INSPECT REAR FIRING<br>PIN HOLE FOR CHAMFER<br>IN BOLT HEAD                                                                         |                     | 6/19/08 | RP         |
|      | C) INSPECT EJECTOR<br>HOLE FOR CHAMFER                                                                                                 |                     | 6/19/08 | RP         |
|      | D) OIL FIRING PIN ASSEMBLY                                                                                                             |                     | 6/24/08 | L.P.D.     |
|      | E) ADJUST TRIGGER PULL<br>TO MIN. SETTING AND<br>STAKE <span style="border: 1px solid black; padding: 2px;">2.50 LBS +/- .5 LBS</span> |                     |         |            |

F004 REV 5/2006


| OP #         | OPERATION NAME                                                           | READINGS                                                    | DATE    | INITIAL |
|--------------|--------------------------------------------------------------------------|-------------------------------------------------------------|---------|---------|
| 560          | F) SAFETY ON FORCE <span>2 LBS MIN<br/>10 LBS MAX</span>                 | <u>5</u> <u>5</u> <u>5</u> <sup>5</sup>                     | 7/7/08  | Fm      |
| CONT.        |                                                                          |                                                             |         |         |
|              | G) SAFETY OFF FORCE <span>2 LBS MIN</span>                               | <u>4</u> <u>4</u> <u>4</u> <sup>5</sup>                     | 7/7/08  | Fm      |
|              | H) TRIGGER PULL TEST<br>AND RETAINABILITY                                |                                                             |         |         |
|              | I) FIRING PIN INDENT <span>.020 MIN</span>                               | <u>.022</u> <u>.022</u> <u>.022</u>                         | 7/7/08  | Fm      |
|              | J) ASSEMBLE STOCK                                                        |                                                             | 6/24/08 | L.P.D.  |
|              | K) ASSEMBLE SWIVEL<br>STUDS                                              |                                                             | 7/19/08 | L.P.D.  |
|              | L) ATTACH FRONT AND<br>REAR SIGHT ASSY'S                                 |                                                             | 7/19/08 | L.P.D.  |
|              | M) IRON SIGHT<br>ALIGNMENT                                               |                                                             | 7/19/08 | L.P.D.  |
|              | N) DETACH FRONT AND<br>REAR SIGHTS AND PLACE<br>IN NUMBERED CONTAINER    |                                                             | 7/19/08 | L.P.D.  |
| 640 &<br>650 | FUNCTION TEST AND<br>TARGET                                              | <u>PASS</u> FAIL<br><u>PASS</u> FAIL                        | 6-29-08 | TRW     |
|              | MALFUNCTION                                                              | CORRECTION                                                  |         |         |
|              | MALFUNCTION                                                              | CORRECTION                                                  |         |         |
|              | MALFUNCTION                                                              | CORRECTION                                                  |         |         |
|              | MALFUNCTION                                                              | CORRECTION                                                  |         |         |
| 660          | INSPECT FOR LIVE AMMO                                                    |                                                             | 6-29-08 | MEM     |
| 670          | FINAL INSPECTION<br>A) HEADSPACE                                         |                                                             | 7/16/08 | Fm      |
|              | B) TRIGGER PULL <span>+/- .5 LBS<br/>MIN 2.50 LBS<br/>MAX 4.0 LBS</span> | <u>2.32</u> <u>2.25</u> <u>2.27</u> <u>2.25</u> <u>2.34</u> | 6/30/08 | RP      |
|              | C) FUNCTION                                                              |                                                             | 7/14/08 | Fm      |
| 690          | PACK                                                                     |                                                             | 7/30/08 | Fm      |

F004 REV 5/2006

## Trigger Profile [ lbs,inch ]

Profile SWS  
 GunType: Rifle  
 Make: Remington  
 Note: R. Putch 6/24/08

Model: M/24  
 Serial No: Form #F005  
 Trigger: 2.5 lbs. ini. +/- .50 lbs.




| # | Peak Force | Travel To Actuate | Initial Take-up | Overtravel | Energy To Actuate | Lock Time | Action Type |
|---|------------|-------------------|-----------------|------------|-------------------|-----------|-------------|
| 1 | 2.532      | 0.054             | 0.037           | 0.038      | 0.044             |           | Set Trigger |
| 2 | 2.555      | 0.054             | 0.037           | 0.038      | 0.044             |           | Set Trigger |
| 3 | 2.555      | 0.054             | 0.037           | 0.038      | 0.044             |           | Set Trigger |
| 4 | 2.499      | 0.054             | 0.037           | 0.038      | 0.043             |           | Set Trigger |
| 5 | 2.521      | 0.054             | 0.037           | 0.038      | 0.044             |           | Set Trigger |

AVG 2.53

## Trigger Profile [ lbs,inch ]

Profile SWS  
 GunType: Rifle  
 Make: Remington  
 Note: R. Putch 6/24/08

Model: M/24  
 Serial No: Form #F005  
 Trigger: 2.5 lbs. after 50 cycles +/- .50 lbs.




| # | Peak Force | Travel To Actuate | Initial Take-up | Overtravel | Energy To Actuate | Lock Time | Action Type |
|---|------------|-------------------|-----------------|------------|-------------------|-----------|-------------|
| 1 | 2.628      | 0.051             | 0.034           | 0.037      | 0.044             |           | Set Trigger |
| 2 | 2.617      | 0.051             | 0.034           | 0.037      | 0.045             |           | Set Trigger |
| 3 | 2.593      | 0.052             | 0.034           | 0.037      | 0.045             |           | Set Trigger |
| 4 | 2.592      | 0.051             | 0.034           | 0.037      | 0.043             |           | Set Trigger |
| 5 | 2.585      | 0.051             | 0.034           | 0.037      | 0.044             |           | Set Trigger |

Avg 2.60

## Trigger Profile [ lbs,inch ]

Profile: SWS  
 GunType: Rifle  
 Make: Remington  
 Note: R. Putch 6/24/08

Model: M/24  
 Serial No: Form #F005  
 Trigger: 3.0 lbs. ini. +/- .75 lbs.




| # | Peak Force | Travel To Actuate | Initial Take-up | Overtravel | Energy To Actuate | Lock Time | Action Type |
|---|------------|-------------------|-----------------|------------|-------------------|-----------|-------------|
| 1 | 3.090      | 0.052             | 0.032           | 0.035      | 0.055             |           | Set Trigger |
| 2 | 3.019      | 0.050             | 0.033           | 0.036      | 0.051             |           | Set Trigger |
| 3 | 3.022      | 0.050             | 0.033           | 0.036      | 0.052             |           | Set Trigger |
| 4 | 3.061      | 0.050             | 0.033           | 0.036      | 0.051             |           | Set Trigger |
| 5 | 3.050      | 0.050             | 0.033           | 0.036      | 0.051             |           | Set Trigger |

Avg 3.04

## Trigger Profile [ lbs,inch ]

Profile SWS  
 GunType: Rifle  
 Make: Remington  
 Note: R. Putch 6/24/08

Model: M/24  
 Serial No: Form #F005  
 Trigger: 3.0 lbs. after 20 cycles +/- .75 lbs.



| # | Peak Force | Travel To Actuate | Initial Take-up | Overtravel | Energy To Actuate | Lock Time | Action Type |
|---|------------|-------------------|-----------------|------------|-------------------|-----------|-------------|
| 1 | 3.085      | 0.050             | 0.032           | 0.035      | 0.053             |           | Set Trigger |
| 2 | 3.129      | 0.051             | 0.032           | 0.035      | 0.054             |           | Set Trigger |
| 3 | 3.142      | 0.050             | 0.033           | 0.035      | 0.053             |           | Set Trigger |
| 4 | 3.159      | 0.050             | 0.033           | 0.035      | 0.053             |           | Set Trigger |
| 5 | 3.193      | 0.051             | 0.032           | 0.035      | 0.054             |           | Set Trigger |


Avg 3.14



## Trigger Profile [ lbs,inch ]

Profile SWS  
 GunType: Rifle  
 Make: Remington  
 Note: R. Putsch 6/24/08

Model: M/24  
 Serial No: Form #F005  
 Trigger: 4.0 lbs. ini. +/- 1.0 lbs.




| # | Peak Force | Travel To Actuate | Initial Take-up | Overtravel | Energy To Actuate | Lock Time | Action Type |
|---|------------|-------------------|-----------------|------------|-------------------|-----------|-------------|
| 1 | 4.117      | 0.054             | 0.035           | 0.035      | 0.074             |           | Set Trigger |
| 2 | 4.147      | 0.054             | 0.035           | 0.035      | 0.073             |           | Set Trigger |
| 3 | 4.123      | 0.054             | 0.035           | 0.035      | 0.074             |           | Set Trigger |
| 4 | 4.209      | 0.054             | 0.035           | 0.035      | 0.075             |           | Set Trigger |
| 5 | 4.164      | 0.053             | 0.035           | 0.036      | 0.072             |           | Set Trigger |

AVG 4.15

## Trigger Profile [ lbs,inch ]

Profile SWS  
 GunType: Rifle  
 Make: Remington  
 Note: R. Putch 6/24/08

Model: M/24  
 Serial No: Form #F005  
 Trigger: 4.0 lbs. after 20 cycles +/- 1.0 lbs.




| # | Peak Force | Travel To Actuate | Initial Take-up | Overtravel | Energy To Actuate | Lock Time | Action Type |
|---|------------|-------------------|-----------------|------------|-------------------|-----------|-------------|
| 1 | 4.083      | 0.054             | 0.034           | 0.035      | 0.073             |           | Set Trigger |
| 2 | 4.177      | 0.054             | 0.035           | 0.035      | 0.074             |           | Set Trigger |
| 3 | 4.174      | 0.054             | 0.035           | 0.035      | 0.074             |           | Set Trigger |
| 4 | 4.181      | 0.054             | 0.034           | 0.035      | 0.075             |           | Set Trigger |
| 5 | 4.197      | 0.053             | 0.035           | 0.035      | 0.073             |           | Set Trigger |

Avg 4.16

## Trigger Profile [ lbs,inch ]

Profile SWS  
GunType: Rifle  
Make: Remington  
Note: R. Putch 6/24/08

Model: M/24  
Serial No: Form #F005  
Trigger: reset to 2.5 lbs. +/- .50 lbs. for final test




| # | Peak Force | Travel To Actuate | Initial Take-up | Overtravel | Energy To Actuate | Lock Time | Action Type |
|---|------------|-------------------|-----------------|------------|-------------------|-----------|-------------|
| 1 | 2.526      | 0.053             | 0.035           | 0.037      | 0.044             |           | Set Trigger |
| 2 | 2.518      | 0.053             | 0.036           | 0.037      | 0.044             |           | Set Trigger |
| 3 | 2.534      | 0.053             | 0.036           | 0.037      | 0.043             |           | Set Trigger |
| 4 | 2.601      | 0.053             | 0.035           | 0.037      | 0.045             |           | Set Trigger |
| 5 | 2.555      | 0.053             | 0.036           | 0.037      | 0.044             |           | Set Trigger |

Avg 2.54

## Trigger Profile [ lbs,inch ]

Profile SWS  
 GunType: Rifle  
 Make: Remington  
 Note: R. Putch 6/24/08

Model: M/24  
 Serial No: Form #F005  
 Trigger: set to 4.0 lbs. +/- 1.0 lbs. for target & accuracy



| # | Peak Force | Travel To Actuate | Initial Take-up | Overtravel | Energy To Actuate | Lock Time | Action Type |
|---|------------|-------------------|-----------------|------------|-------------------|-----------|-------------|
| 1 | 4.147      | 0.052             | 0.033           | 0.034      | 0.072             |           | Set Trigger |
| 2 | 4.130      | 0.053             | 0.033           | 0.034      | 0.074             |           | Set Trigger |
| 3 | 4.109      | 0.052             | 0.033           | 0.034      | 0.072             |           | Set Trigger |
| 4 | 4.136      | 0.053             | 0.033           | 0.034      | 0.074             |           | Set Trigger |
| 5 | 4.220      | 0.054             | 0.033           | 0.034      | 0.076             |           | Set Trigger |

Avg 4.14