

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-1

TLW #: TLW1216

Date: 8 / 20 / 03Inspector: SW/BLRound Level: 221☒ Measure Headspace Min +.003.☒ Sear Engagement: 1st. .0282 2nd. .0280 3rd. .0279 Ave. .02803 spec- .020" to .025"☒ Reset Sear Engagement if Required: 1st. .0241 2nd. .0244 3rd. .0242 Ave. .02423☒ Trigger Pull: 1st. 4.535 2nd. 4.386 3rd. 4.638 Ave. 4.520 spec- 4 lb. to 5.5 lb.☒ Reset Trigger Pull if Required: 1st. 4.746 2nd. 4.920 3rd. 4.836 Ave. 4.834☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: Normal Wear, wear on bolt stop.☒ Inspect stock for any signs of cracking or other failure. Lower corner of recoil bracket has cracks on stock, crack on middle take down screw hole.☒ Other items of note: Wear on bolt stop, Top of magazine Box has some protrusion.

TLW1216

Remington Confidential

ET22410