

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-6

TLW #: TLW1216

Date: 8 / 20 / 03

Inspector: SW/BL

Round Level: 221

☒ Measure Headspace min +.006

☒ Sear Engagement: 1st. .0263 2nd. .0262 3rd. .0264 Ave. .02630 spec- .020" to .025" 83

☒ Reset Sear Engagement if Required: 1st. .0234 2nd. .0237 3rd. .0235 Ave. .02353

☒ Trigger Pull: 1st. 5.353 2nd. 5.274 3rd. 5.220 Ave. 5.282 spec- 4 lb. to 5.5 lb.

☒ Reset Trigger Pull if Required: 1st. 4.934 2nd. 5.106 3rd. 4.826 Ave. 4.955

☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: wear on bolt stop

☒ Inspect stock for any signs of cracking or other failure. Lower corner of recoil bracket has cracks on stock
Crack on middle take down screw hole

☒ Other items of

note: Top of magazine box has some protrusion, wear in
magazine latch area

TLW1216

Remington Confidential

ET22427