

CONFIDENTIAL

Remington Arms Company Inc.
Research & Development Technical Center
315 West Ring Road
Elizabethtown, KY 42701

Clean & Inspect Checklist

Model: 710 Magnum

Project: 241314

Rifle: A-6

TLW #: TLW1216

Date: 9 / 22 / 03

Inspector: SW/JS

Round Level: 1761

☒ Measure Headspace MINT + .006

☒ Sear Engagement: 1st. .0235 2nd. .0239 3rd. .0236 Ave. .0236 spec. .020" to .025" 83

☐ Reset Sear Engagement if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____

☒ Trigger Pull: 1st. 4.609 2nd. 4.716 3rd. 4.732 Ave. 4.685 spec. 4 lb. to 5.5 lb.

☐ Reset Trigger Pull if Required: 1st. _____ 2nd. _____ 3rd. _____ Ave. _____

☒ Inspect cam surface, locking lugs and bolt stop for signs of excessive wear: NORMAL WEAR, WEAR ON BOLT STOP

☒ Inspect stock for any signs of cracking or other failure: CRACKS IN STOCK

☒ Other items of

note: TOP OF MAGAZINE BOX HAS SOME PROTRUSION WEAR IN MAGAZINE LATCH AREA

TLW1216

Remington Confidential

ET22446